

# KSED95AE

**Product family** 

**Hood Type** Decorative wall hood

Hood

Design Chimney Extraction Extraction Material Painted material Brushed

Type of steel

**EAN** code 8017709212209

Hood width 90 cm



#### **Aesthetics**

Universale **Embossed Aesthetic** Logo

Colour Anthracite

#### **Controls**

Control setting Slider

### **Programs / Functions**

3 No. of speeds

#### **Technical Features**



No. of lights 2 Anti-grease filters Aluminium Light type **LED** Charcoal filters included Yes **Light Power** 1 W Vent outlet 150 mm Light color temperature 4000 °K Minimum distance from 750 mm

scale (°K) **GAS** hob

Free outlet maximum 595 m<sup>3</sup>/h Minimum distance from 650 mm capacity **ELECTRIC hob** 

Motor power 200 W Non return valve Yes No. of filters 3



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	328	50
Speed 2	420	57
Speed 3	588	65

### Performance / Energy Label

**Annual Efficiency** 54 kWh/a Airbourne acouistical A- 50 dB(A) weighted sound Power Consumption (AEChood) Emission at minimum Energy efficieency class B speed (SPEmin) (EEC) Airborne acoustical A-65 dB(A) Fluid Dynamic Efficiency 25,3 weighted sound Power (FDE) Emission at maximum Fluid Dynamic Efficiency B speed (SPEmax) class (FDEC) Time increase factor (F) Lighting Efficiency (LE) 74,3 lux/W **Energy Efficiency Index** 61.2 Lighting Efficiency Class A Measured air flow rate 318 m<sup>3</sup>/h (LEC) at best efficiency point **Grease Filtering** 70,8 % (Qbep) Efficiency (GFE) Measured air pressure 375 Pa **Grease Filtering** D at best efficiency point Efficiency Class (GFEC) (Pbep) Air flow at minumum 328 m<sup>3</sup>/h Measured electric 131 W speed (Qmin) power input at best Air flow at maximum 588 m<sup>3</sup>/h efficiency point (Wbep) speed (Qmax) **Nominal Power** 2 W consumption of the light system (WL) Average illumination of 164 lux the light on the cooking surface (Emiddle)

#### **Electrical Connection**

Electrical connection 202 W Frequency (Hz) 50-60 Hz rating Power supply cable 1000 mm Voltage 220-240 V length

#### Also available


Alternative coloursBlack, Stainless steel,<br/>availibleAvailable coloursKSED95NEE - KSED95XE -<br/>KSED95PE - KSED95RWE

Sound power level at

highest setting (Lwa)

65 dB(A)







### Not included accessories

FLT6



Round Charcoal filters (kit 2 pieces)



#### **KITALLFC**

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



## Symbols glossary (TT)



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



B: Product energy rating, measured from A+++ to D / G depending on the product family.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.