

# KSED95MBL

## Product family

**Hood Type** Chimney Cooker Hoods

**Design** Chimney

**Extraction** Ducted out or re-circulation possible

**Material** Painted material

**Type of steel** Brushed

**EAN code** 8017709346324

**Hood width** 90 cm

**Aesthetics** Victoria

**Colour** Matte Black

**Finishing** Black

**Logo** Silk screen



## Controls

**Control setting** Slider

## Program / Functions

**No. of speeds** 3

## Technical Features



**No. of lights**

2

**No. of filters**

3

**Light type**

LED

**Anti-grease filters**

Aluminium

**Light power**

1 W

**Vent outlet**

150 mm

**Light colour**

4000 K

**Minimum distance from GAS hob**

750 mm

**temperature scale (K)**

595 m<sup>3</sup>/h

**Minimum distance from ELECTRIC hob**

650 mm

**Free outlet maximum capacity**

200 W

**Non return valve**

Yes

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	328	50
Speed 2	420	57

Speed 3	588	65
---------	-----	----

## Performance / Energy Label



<b>Annual Efficiency Consumption (AEChood)</b>	54 kWh/year	<b>Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)</b>	50 dBA
<b>Energy efficiency class ( B EEC)</b>		<b>Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)</b>	65 dBA
<b>Fluid Dynamic Efficiency (FDE)</b>	25.3	<b>Time increase factor (F)</b>	1.1
<b>Fluid Dynamic Efficiency class (FDEC)</b>	B	<b>Energy Efficiency Index per first cavity</b>	61.2
<b>Lighting Efficiency (LE)</b>	74 lux/W	<b>Measured air flow rate at best efficiency point (Qbep)</b>	318.4 m <sup>3</sup> /h
<b>Lighting Efficiency Class (LEC)</b>	A	<b>Measured air pressure at best efficiency point (Qbep)</b>	375 Pa
<b>Grease Filtering Efficiency (GFE)</b>	70.8 %	<b>Measured electric power input at best efficiency point (Wbep)</b>	131 W
<b>Grease Filtering Efficiency Class (GFEC)</b>	D	<b>Normal Power of the light system (WI)</b>	2.2 W
<b>Air flow at minimum speed (Qmin)</b>	328 m <sup>3</sup> /h	<b>Average illumination of the light on the cooking surface (Emiddle)</b>	164 lux
<b>Maximum extraction rate</b>	588 m <sup>3</sup> /h	<b>Sound power level at highest setting (Lwa)</b>	65 dBA

## Electrical Connection

<b>Nominal power</b>	202 W	<b>Power supply cable length</b>	1000 mm
<b>Voltage</b>	220-240 V		
<b>Frequency (Hz)</b>	50-60 Hz	<b>Plug</b>	No

## Also available

**Alternative colours available** Stainless steel, Anthracite, Red Wine **Available colours** KSED95XE - KSED95AE - KSED95RWE

## Compatible Accessories

---

### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.