# KSED95MBL

| | |
|---|---|
| **Product family** | Hood |
| **Hood Type** | Chimney Cooker Hoods |
| **Design** | Chimney |
| **Extraction** | Ducted out or re-circulation possible |
| **Material** | Painted material |
| **Type of steel** | Brushed |
| **EAN code** | 8017709346324 |
| **Hood width** | 90 cm |
| **Aesthetics** | Victoria |
| **Colour** | Matte Black |
| **Finishing** | Black |
| **Logo** | Silk screen |



## Controls

| | |
|---|---|
| **Control setting** | Slider |

## Program / Functions

| | |
|---|---|
| **No. of speeds** | 3 |

## Technical Features

| | | | |
|---|---|---|---|
| **No. of lights** | 2 | **No. of filters** | 3 |
| **Light type** | LED | **Anti-grease filters** | Aluminium |
| **Light power** | 1 W | **Vent outlet** | 150 mm |
| **Light colour temperature scale (K)** | 4000 K | **Minimum distance from GAS hob** | 750 mm |
| **Free outlet maximum capacity** | 595 m³/h | **Minimum distance from ELECTRIC hob** | 650 mm |
| **Motor power** | 200 W | **Non return valve** | Yes |

| | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704-2-13 [dBA] |
|---|---|---|
| Speed 1 | 328 | 50 |
| Speed 2 | 420 | 57 |

| | | |
|---|---|---|
| Speed 3 | 588 | 65 |

## Performance / Energy Label



| | |
|---|---|
| **Annual Efficiency Consumption (AEChood)** | 54 kWh/year |
| **Energy efficiency class ( EEC)** | B |
| **Fluid Dynamic Efficiency (FDE)** | 25,3 |
| **Fluid Dynamic Efficiency class (FDEC)** | B |
| **Lighting Efficiency (LE)** | 74 lux/W |
| **Lighting Efficiency Class (LEC)** | A |
| **Grease Filtering Efficiency (GFE)** | 70,8 % |
| **Grease Filtering Efficiency Class (GFEC)** | D |
| **Air flow at minumum speed (Qmin)** | 328 m³/h |
| **Maximum extraction rate** | 588 m³/h |
| **Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)** | 50 dBA |
| **Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)** | 65 dBA |
| **Time increase factor (F)** | 1,1 |
| **Energy Efficiency Index per first cavity** | 61,2 |
| **Measured air flow rate at best efficiency point (Qbep)** | 318,4 m³/h |
| **Measured air pressure at best efficiency point (Qbep)** | 375 Pa |
| **Measured electric power input at best efficiency point (Wbep)** | 131 W |
| **Normal Power of the light system (WI)** | 2,2 W |
| **Average illumination of the light on the cooking surface (Emiddle)** | 164 lux |
| **Sound power level at highest setting (Lwa)** | 65 dBA |

## Electrical Connection

| | |
|---|---|
| **Nominal power** | 202 W |
| **Voltage** | 220-240 V |
| **Frequency (Hz)** | 50-60 Hz |
| **Power supply cable length** | 1000 mm |
| **Plug** | No |

## Also available

| | |
|---|---|
| **Alternative colours availible** | Stainless steel, Anthracite, Red Wine |
| **Available colours** | KSED95XE - KSED95AE - KSED95RWE |

## Compatible Accessories



**FLT6**

Round Charcoal filters (kit 2 pieces)



**KITALLFC**

Universal Charcoal filter  Stainless Steel AISI 304  The filter can be washed in dishwasher 50 °C (water and suitable detergent)  and to dry it put in the oven 180°C 25 minutes

# Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

