

# KSED95MBL

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Painted material
Type of steel	Brushed
EAN code	8017709346324
Hood width	90 cm
Aesthetic	Victoria
Colour	Matt Black
Finishing	Black
Logo	Silk screen



## Controls

Control setting	Slider
-----------------	--------

## Program / Functions

No. of speeds	3
---------------	---

## Technical Features

			
No. of lights	2	No. of filters	3
Light type	LED	Anti-grease filters	Aluminium
Light Power	1 W	Vent outlet	150 mm
Light color temperature scale (K)	4000 K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	595 m <sup>3</sup> /h	Minimum distance from ELECTRIC hob	650 mm
Motor power	200 W	Non return valve	Yes

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	328	50
Speed 2	420	57

Speed 3	588	65
------------	-----	----

## Performance / Energy Label



Annual Efficiency Consumption (AEC <sub>hood</sub> )	54 kWh/a	Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPE <sub>min</sub> )	50 dBA
Energy efficiency class (EEC)	B	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE <sub>max</sub> )	65 dBA
Fluid Dynamic Efficiency (FDE)	25.3	Time increase factor (F)	1.1
Fluid Dynamic Efficiency class (FDEC)	B	Energy Efficiency Index	61.2
Lighting Efficiency (LE)	74 lux/W	Measured air flow rate at best efficiency point (Q <sub>bep</sub> )	318.4 m <sup>3</sup> /h
Lighting Efficiency Class (LEC)	A	Measured air pressure at best efficiency point (P <sub>bep</sub> )	375 Pa
Grease Filtering Efficiency (GFE)	70.8 %	Measured electric power input at best efficiency point (W <sub>bep</sub> )	131 W
Grease Filtering Efficiency Class (GFEC)	D	Nominal Power consumption of the light system (WL)	2.2 W
Air flow at minumum speed (Q <sub>min</sub> )	328 m <sup>3</sup> /h	Average illumination of the light on the cooking surface (E <sub>middle</sub> )	164 lux
Air flow at maximum speed (Q <sub>max</sub> )	588 m <sup>3</sup> /h	Sound power level at highest setting (L <sub>wa</sub> )	65 dBA

## Electrical Connection

Electrical connection rating	202 W	Power supply cable length	1000 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		

## Also available

Alternative colours available	Stainless steel, Anthracite, Red Wine	Available colours	KSED95XE - KSED95AE - KSED95RWE
-------------------------------	---------------------------------------	-------------------	---------------------------------

---

## Compatible Accessories

---

### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.