

# KSED95XE

|                       |                                       |
|-----------------------|---------------------------------------|
| <b>Product family</b> | Hood                                  |
| <b>Hood Type</b>      | Chimney Cooker Hoods                  |
| <b>Design</b>         | Chimney                               |
| <b>Extraction</b>     | Ducted out or re-circulation possible |
| <b>Material</b>       | Stainless steel                       |
| <b>Type of steel</b>  | Brushed                               |
| <b>EAN code</b>       | 8017709206109                         |
| <b>Hood width</b>     | 90 cm                                 |
| <b>Aesthetics</b>     | Universal                             |
| <b>Colour</b>         | Stainless steel                       |
| <b>Finishing</b>      | Brushed                               |
| <b>Logo</b>           | Embossed                              |



## Controls

|                        |        |
|------------------------|--------|
| <b>Control setting</b> | Slider |
|------------------------|--------|

## Program / Functions

|                      |   |
|----------------------|---|
| <b>No. of speeds</b> | 3 |
|----------------------|---|

## Technical Features

|  |   |   |           |
|--|---|---|-----------|
|  |  |   |           |
| <b>No. of lights</b>   | 2   | <b>No. of filters</b>                     | 3         |
| <b>Light type</b>  | LED   | <b>Anti-grease filters</b>                | Aluminium |
| <b>Light power</b>   | 1 W   | <b>Vent outlet</b>                        | 150 mm    |
| <b>Light colour temperature scale (K)</b>  | 4000 K  | <b>Minimum distance from GAS hob</b>      | 750 mm    |
| <b>Free outlet maximum capacity</b>  | 595 m <sup>3</sup> /h   | <b>Minimum distance from ELECTRIC hob</b> | 650 mm    |
| <b>Motor power</b>   | 200 W   | <b>Non return valve</b>                   | Yes       |

|         | Extraction rate IEC 61591 [m <sup>3</sup> /h] | Noise level IEC 60704-2-13 [dBA] |
|---------|---|----------------------------------|
| Speed 1 | 328   | 50                               |
| Speed 2 | 420   | 57                               |

|            |     |    |
|------------|-----|----|
| Speed<br>3 | 588 | 65 |
|------------|-----|----|

## Performance / Energy Label



|  |                       |  |                       |
|--|-----------------------|--|-----------------------|
| Annual Efficiency Consumption (AEChood)  | 54 kWh/year           | Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) | 50 dBA                |
| Energy efficiency class (EEC)            | B                     | Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)  | 65 dBA                |
| Fluid Dynamic Efficiency (FDE)           | 25,3                  | Time increase factor (F)   | 1,1                   |
| Fluid Dynamic Efficiency class (FDEC)    | B                     | Energy Efficiency Index per first cavity                                       | 61,2                  |
| Lighting Efficiency (LE)                 | 74,3 lux/W            | Measured air flow rate at best efficiency point (Qbep)                         | 318 m <sup>3</sup> /h |
| Lighting Efficiency Class (LEC)          | A                     | Measured air pressure at best efficiency point (Qbep)                          | 375 Pa                |
| Grease Filtering Efficiency (GFE)        | 70,8 %                | Measured electric power input at best efficiency point (Wbep)                  | 131 W                 |
| Grease Filtering Efficiency Class (GFEC) | D                     | Normal Power of the light system (WI)  | 2 W                   |
| Air flow at minumum speed (Qmin)         | 328 m <sup>3</sup> /h | Average illumination of the light on the cooking surface (Emiddle)             | 164 lux               |
| Maximum extraction rate                  | 588 m <sup>3</sup> /h | Sound power level at highest setting (Lwa)                                     | 65 dBA                |

## Electrical Connection

|                |           |                           |         |
|----------------|-----------|---------------------------|---------|
| Nominal power  | 202 W     | Power supply cable length | 1000 mm |
| Voltage        | 220-240 V | Plug                      | No      |
| Frequency (Hz) | 50-60 Hz  |                           |         |

## Also available

|                               |                                    |                   |   |
|-------------------------------|------------------------------------|-------------------|---|
| Alternative colours available | Black, Anthracite, Cream, Red Wine | Available colours | KSED95NEE - KSED95AE - KSED95PE - KSED95RWE |
|-------------------------------|------------------------------------|-------------------|---|



---

## Compatible Accessories

---

### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.