# KSEG58PXE



| | |
|---|---|
| **Product family** | Hood |
| **Hood Type** | Integrated hood |
| **Design** | Fully integrated |
| **Extraction** | Extraction |
| **Electronic control** | Yes |
| **Perimeter extraction** | Yes |
| **Material** | Stainless steel |
| **Type of steel** | Brushed |
| **EAN code** | 8017709224912 |
| **Hood width** | 54 cm |
| **Aesthetic** | Universale |
| **Colour** | Stainless steel |
| **Finishing** | Satin |
| **Logo** | Embossed |

## Controls

| | | | |
|---|---|---|---|
| **Control setting** | Electronic buttons | **Led color** | White |

## Program / Functions

| | |
|---|---|
| **No. of speeds** | 3 |
| **Intensive speed** | BOOST |
| **Time-setting options** | |

## Technical Features

| | | | |
|---|---|---|---|
| **No. of lights** | 2 | **Anti-grease filters** | Aluminium |
| **Light type** | LED | **Filter replacement indicator** | Yes |
| **Light Power** | 1 W | **Vent outlet** | 150 mm |
| **Light color temperature (K)** | 4000 K | **Minimum distance from GAS hob** | 750 mm |
| **Free outlet maximum capacity** | 673 m³/h | **Minimum distance from ELECTRIC hob** | 500 mm |
| **Motor power** | 275 W | **Non return valve** | Yes |
| **No. of filters** | 2 | | |

| | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704-2-13 [dBA] |
|---|---|---|
| Speed 1 | 261 | 46 |

| | | |
|---|---|---|
| Speed 2 | 436 | 58 |
| Speed 3 | 606 | 65 |
| Intensive speed | 683 | 68 |

## Performance / Energy Label




| | |
|---|---|
| **Annual Efficiency Consumption (AEChood)** | 46 kWh/a |
| **Energy efficicency class (EEC)** | A |
| **Fluid Dynamic Efficiency (FDE)** | 31,7 |
| **Fluid Dynamic Efficiency class (FDEC)** | A |
| **Lighting Efficiency (LE)** | 111,8 lux/W |
| **Lighting Efficiency Class (LEC)** | A |
| **Grease Filtering Efficiency (GFE)** | 56,9 % |
| **Grease Filtering Efficiency Class (GFEC)** | E |
| **Air flow at minumum speed (Qmin)** | 261 m³/h |
| **Air flow at maximum speed (Qmax)** | 606 m³/h |
| **Air flow at boost speed (Qboost)** | 683 m³/h |

| | |
|---|---|
| **Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)** | 46 dBA |
| **Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)** | 65 dBA |
| **Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)** | 68 dBA |
| **Time increase factor (F)** | 0,9 |
| **Energy Efficiency Index** | 50,7 |
| **Measured air flow rate at best efficiency point (Qbep)** | 329 m³/h |
| **Measured air pressure at best efficiency point (Pbep)** | 466 Pa |
| **Measured electric power input at best efficiency point (Wbep)** | 134 W |
| **Nominal Power consumption of the light system (WL)** | 2 W |
| **Average illumination of the light on the cooking surface (Emiddle)** | 246 lux |
| **Sound power level at highest setting (Lwa)** | 65 dBA |


## Electrical Connection

| | |
|---|---|
| **Electrical connection rating** | 277 W |
| **Voltage** | 220-240 V |
| **Frequency (Hz)** | 50-60 Hz |

| | |
|---|---|
| **Power supply cable length** | 1500 mm |
| **Plug** | Not present |


7
76,5
333,5
min.30-max.45
264
490
38
Ø150
194
106
272
370
300
194
106
540

## Compatible Accessories



**FLT4**

Charcoal filter Kit 1 piece

## Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.




Intensive/turbo setting: when extra fast extraction is required.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Perimeter extraction panels: very efficient and aid noise reduction.