

## KSET66VNE3

Product family	Hood
Tipo de Exaustor	Integrated (semi) hood
Design	Telescopic
Extraction	Extraction
Electronic control	No
Perimeter extraction	No
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709349233
Hood width	60 cm
Aesthetic	Universal
Colour	Black
Acabamento	Satin
Glass Type	Black
Cor da serigrafia	Serigrafia em branco
Logotipo	Logotipo serigrafado

## Controls

Control setting	Slider
-----------------	--------

## Program / Functions

No. of speeds	3
Intensive speed	No
24h air filter function	No
Other functions	No
Time-setting options	No
Other options	No
Ventilação automática	No
Ventilação automática 2.0	No

## Technical Features



Hood without motor	No	No. of filters	2
Remote motor	No	Anti-grease filters	Aluminium
No. of lights	2	Charcoal filters included	No
Light type	LED	Filter replacement indicator	No
Light Power	1 W	Vent outlet	150 mm
Dimmer mode	No	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	640 m <sup>3</sup> /h		
Motor power	160 W		

Minimum distance from ELECTRIC hob 650 mm  
Non return valve No

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	260	47
Speed 2	400	54
Speed 3	610	63

## Accessories Included

Remote control No  
Sliding door No  
Tube reduction No

## Performance / Energy Label



Consumo anual de energia (CAE exaustor)	79 kWh/a	Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)	47 dBA
Energy efficiency class (EEC)	C	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	63 dBA
Fluid Dynamic Efficiency (FDE)	18,3	Time increase factor (F)	1,3
Fluid Dynamic Efficiency class (FDEC)	C	Energy Efficiency Index	74,4
Lighting Efficiency (LE)	59 lux/W	Measured air flow rate at best efficiency point (Qbep)	360 m <sup>3</sup> /h
Lighting Efficiency Class (LEC)	A	Measured air pressure at best efficiency point (Pbep)	300 Pa
Grease Filtering Efficiency (GFE)	76 %	Measured electric power input at best efficiency point (Wbep)	164 W
Grease Filtering Efficiency Class (GFEC)	C	Nominal Power consumption of the light system (WL)	2.2 W
Air flow at minumum speed (Qmin)	260 m <sup>3</sup> /h	Average illumination of the light on the cooking surface (Emiddle)	130 lux
Air flow at maximum speed (Qmax)	610 m <sup>3</sup> /h	Sound power level at highest setting (Lwa)	63 dBA

## Electrical Connection

---

<b>Plug</b>	No	<b>Frequency (Hz)</b>	50-60 Hz
<b>Electrical connection rating</b>	162 W	<b>Comprimento do cabo de alimentação</b>	1500 mm
<b>Voltage</b>	220-240 V		

## Also available

---

<b>Outras cores disponíveis</b>	Branca, Aço inox, Vidro Silver	<b>Códigos das outras cores disponíveis</b>	KSET66VBE2 - KSET66E - KSET66VSE2
---------------------------------	--------------------------------	---	-----------------------------------

---

## Compatible Accessories

---

KITFC152

Filtro de carvão Redondo Kit 2 peças



---

## Symbols glossary

---



Filtros: O modelo tem filtros para ajudar a remover a graxa do vapor que emana das panelas durante o cozimento.



Luzes: Todos os exaustores possuem luzes para iluminar a área de cozinhar ou adicionar ao ambiente da cozinha.