

KSG52E

Product family	Hood
Hood Type	Integrated hood
Design	Fully integrated
Extraction	Extraction
Material	Painted material
EAN code	8017709275129
Hood width	54 cm



Aesthetics

Aesthetic Colour	Universale Silver	Serigraphy colour Logo	Black Silk screen
------------------	-------------------	------------------------	-------------------



Controls

Control setting	Slider
-----------------	--------

Programme / Functions

No. of speeds	3
---------------	---

Technical Features

			
No. of lights	2	No. of filters	1
Light type	LED	Anti-grease filters	Aluminium
Light Power	3 W	Vent outlet	120 mm
Light color temperature scale (°K)	2700 °K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	232 m ³ /h	Minimum distance from ELECTRIC hob	500 mm
Motor power	75 W	Non return valve	Yes

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	125	45
Speed 2	155	47
Speed 3	224	54


Performance / Energy Label

C

Annual Efficiency Consumption (AEChood)	50 kWh/a	Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)	45 dB(A)
Energy efficiency class (EEC)	C	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	54 dB(A)
Fluid Dynamic Efficiency (FDE)	8.8	Time increase factor (F)	1.7
Fluid Dynamic Efficiency class (FDEC)	E	Energy Efficiency Index	84.7
Lighting Efficiency (LE)	13 lux/W	Measured air flow rate at best efficiency point (Qbep)	160 m ³ /h
Lighting Efficiency Class (LEC)	D	Measured air pressure at best efficiency point (Pbep)	145 Pa
Grease Filtering Efficiency (GFE)	56 %	Measured electric power input at best efficiency point (Wbep)	74 W
Grease Filtering Efficiency Class (GFEC)	E	Nominal Power consumption of the light system (WL)	6 W
Air flow at mininum speed (Qmin)	125 m ³ /h	Average illumination of the light on the cooking surface (Emiddle)	78 lux
Air flow at maximum speed (Qmax)	224 m ³ /h	Sound power level at highest setting (Lwa)	54 dB(A)

Electrical Connection

Electrical connection rating	81 W	Frequency (Hz)	50-60 Hz
Voltage	220-240 V	Power supply cable length	1500 mm



Not included accessories



KITFC62

Charcoal filter round (kit 2 pieces)

Symbols glossary (TT)



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



C: Product energy rating



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.