

KSG6P4X







Product family	Hood
Hood Type	Integrated hood
Design	Fully integrated
Extraction	Extraction
Electronic control	Yes
Perimeter extraction	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709319366
Hood width	60 cm
Aesthetic	Universale
Colour	Stainless steel
Finishing	Satin
Logo	Silk screen








Controls

Control setting	Touch control back-lighted White	Led color	White
-----------------	-------------------------------------	-----------	-------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-vent 2.0	

Technical Features

				
No. of lights	2	No. of filters	2	
Light type	LED	Anti-grease filters	Aluminium	
Light Power	2.3 W	Filter replacement indicator	Yes	
Dimmer mode	Yes	Vent outlet	150 mm	
Light color temperature range	2700 - 4000 K	Minimum distance from GAS hob	650 mm	
Free outlet maximum capacity	730 m³/h	Minimum distance from ELECTRIC hob	650 mm	
Motor power	230 W	Non return valve	Yes	

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	265	49
Speed 2	360	56
Speed 3	484	61
Intensive speed	660	67

Performance / Energy Label






Annual Efficiency Consumption (AEChood) 58 kWh/a
Energy efficiency class (EEC) B
Fluid Dynamic Efficiency (FDE) 27.9
Fluid Dynamic Efficiency class (FDEC) B
Lighting Efficiency (LE) 39.3 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 74.9 %
Grease Filtering Efficiency Class (GFEC) D
Air flow at minumum speed (Qmin) 265 m³/h
Air flow at maximum speed (Qmax) 484 m³/h
Air flow at boost speed (Qboost) 660 m³/h

Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin) 49 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 62 dBA
Airbourne acouistical A-weighted sound power emission at boost speed (SPEboost) 67 dBA
Time increase factor (F) 1.0
Energy Efficiency Index 58
Measured air flow rate at best efficiency point (Qbep) 348 m³/h
Measured air pressure at best efficiency point (Pbep) 433 Pa
Measured electric power input at best efficiency point (Wbep) 150 W
Nominal Power consumption of the light system (WL) 5 W
Average illumination of the light on the cooking surface (Emiddle) 181 lux
Sound power level at highest setting (Lwa) 62 dBA

Electrical Connection

Electrical connection rating	235 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		



Compatible Accessories



FLT6












Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary

	24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.		Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.
	Connection between hob and hood		Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.
			Dimmering Lights
	Warning light(s): to advise when filters need changing.		Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.
	Perimeter extraction panels: very efficient and aid noise reduction.		Tunable white from warm to cold
	Intensive/turbo setting: when extra fast extraction is required.		