

KSG70HPE

Product family Hood

Hood Type Integrated hood Design Fully integrated Extraction Extraction

Electronic control Yes

Painted material Material

Type of steel Brushed

EAN code 8017709333621

Hood width 72 cm **Aesthetic** Universale Colour Stainless steel

Finishing Satin Serigraphy colour Black Logo Silk screen



Controls

Led color White Control setting **Buttons**

Program / Functions

No. of speeds 3

Technical Features









2 No. of lights Anti-grease filters Charcoal filters included Yes Light type LED Filter replacement **Light Power** 5 W Yes

Light color temperature 2700 K

scale (K)

Free outlet maximum 580 m³/h

capacity

Motor power 175 W

No. of filters 2 Aluminium

indicator

150 mm Vent outlet 650 mm

Minimum distance from **GAS** hob

500 mm

Minimum distance from

ELECTRIC hob

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2- 13 [dBA]
Speed 1	232	44
Speed 2	356	53



Speed 3	584	63
------------	-----	----

Performance / Energy Label

Annual Efficiency 75 kWh/aAirbourne acouistical A- 46 dBA Consumption (AEChood) weighted sound Power **Emission at minimum** Energy efficieency class B speed (SPEmin) (EEC) Airborne acoustical A-65 dBA Fluid Dynamic Efficiency 20,9 weighted sound Power (FDE) **Emission at maximum** Fluid Dynamic Efficiency C speed (SPEmax) class (FDEC) Time increase factor (F) 1,2 Lighting Efficiency (LE) 44,1 lux/W **Energy Efficiency Index** 69,6 Lighting Efficiency Class A Measured air flow rate 345 m³/h (LEC) at best efficiency point **Grease Filtering** 75,1% (Qbep) Efficiency (GFE) Measured air pressure 355 Pa **Grease Filtering** С at best efficiency point **Efficiency Class (GFEC)** (Pbep) Air flow at minumum 225 m³/h Measured electric 163 W speed (Qmin) power input at best Air flow at maximum 580 m³/h efficiency point (Wbep) speed (Qmax) **Nominal Power** 5 W consumption of the light system (WL) Average illumination of 221 lux the light on the cooking surface (Emiddle)

Electrical Connection

Electrical connection 285 W Power supply cable 1000 mm rating length


Voltage 220-240 V Plug Not present Frequency (Hz) 50-60 Hz


Sound power level at


highest setting (Lwa)

65 dBA











Compatible Accessories

KITFC221R

Charcoal filter high efficiency capable to regenerate and last up to 3 years.





Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.