

# KSG8P4MB



**Product family** Hood

**Hood Type** Integrated hood Fully integrated Design Extraction Extraction **Electronic control** Yes

Perimeter extraction Yes

Material Stainless steel Type of steel Brushed

**EAN** code 8017709336295

Hood width 75 cm **Aesthetic** Universale Colour Matt Black **Finishing** Satin Silk screen Logo



#### **Controls**

Control setting Touch control back-lighted Led color White

White

### **Program / Functions**

No. of speeds Intensive speed

24h air filter function

Time-setting options

Auto-vent 2.0









#### **Technical Features**











No. of lights 2 Light type **LED Light Power** 2.3 W Dimmer mode

Light color temperature

range

Free outlet maximum

capacity

Motor power

730 m<sup>3</sup>/h

2700 - 4000 K

230 W

No. of filters

Anti-grease filters

Filter replacement indicator

Vent outlet Minimum distance from

**GAS** hob

Minimum distance from

**ELECTRIC hob** 

Non return valve

650 mm

150 mm

650 mm

Aluminium

Yes

Yes



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	266	46
Speed 2	356	52
Speed 3	480	60
Intensive speed	681	67

### Performance / Energy Label

/	K.
	Ţ

**Annual Efficiency** 53 kWh/a Airbourne acouistical A- 46 dBA Consumption (AEChood) weighted sound Power **Emission at minimum** Energy efficieency class A speed (SPEmin) Airborne acoustical A-60 dBA Fluid Dynamic Efficiency 29.7 weighted sound Power (FDE) Emission at maximum Fluid Dynamic Efficiency A speed (SPEmax) class (FDEC) Airbourne acoustical A- 67 dBA Lighting Efficiency (LE) 38.0 lux/W weighted sound power Lighting Efficiency Class A emission at boost speed (LEC) (SPEboost) **Grease Filtering** 73.8 % Time increase factor (F) Efficiency (GFE) **Energy Efficiency Index** 52.5 **Grease Filtering** D Measured air flow rate 356 m<sup>3</sup>/h Efficiency Class (GFEC) at best efficiency point Air flow at minumum 266 m<sup>3</sup>/h speed (Qmin) Measured air pressure 448 Pa Air flow at maximum 480 m<sup>3</sup>/h at best efficiency point speed (Qmax) (Pbep) Air flow at boost speed 681 m<sup>3</sup>/h Measured electric 149 W (Qboost) power input at best efficiency point (Wbep) **Nominal Power** 5 W consumption of the light system (WL) Average illumination of 175 lux

#### **Electrical Connection**

Electrical connection 235 W

rating

Power supply cable

the light on the cooking surface (Emiddle) Sound power level at

highest setting (Lwa)

length

Plug Not present

60 dBA

1500 mm

#### Also available



Alternative colours available

Stainless steel

Available colours

KSG8P4X



# **Compatible Accessories**

#### FLT6

Round Charcoal filters (kit 2 pieces)





#### **KITALLFC**

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



## Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Perimeter extraction panels: very efficient and aid noise reduction.



Intensive/turbo setting: when extra fast extraction is required.



Connection between hob and hood



**Dimmering Lights** 



Tunable white from warm to cold