

# KSG9P4MB



**Product family** Hood

**Hood Type** Integrated hood Fully integrated Design Extraction Extraction **Electronic control** Yes

Perimeter extraction Yes Material Stainless steel

Type of steel Brushed EAN code 8017709336301

Hood width 90 cm **Aesthetic** Universale Colour Matt Black **Finishing** Satin Silk screen Logo



#### **Controls**

Control setting Touch control back-lighted Led color White

White

## **Program / Functions**

No. of speeds Intensive speed

24h air filter function

Time-setting options

Auto-vent 2.0









### **Technical Features**











2700 - 4000 K

730 m<sup>3</sup>/h

230 W

No. of lights 2 Light type **LED Light Power** 2.3 W Dimmer mode

Light color temperature

range

Free outlet maximum

capacity

Motor power

No. of filters Anti-grease filters Filter replacement

Aluminium Yes

indicator

Vent outlet Minimum distance from

150 mm 650 mm

**GAS** hob

Minimum distance from

650 mm

**ELECTRIC hob** 

Non return valve

Yes

**SMEG SPA** 30/11/2025



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	243	45
Speed 2	362	53
Speed 3	481	59
Intensive speed	697	67

### Performance / Energy Label

A f

**Annual Efficiency** 53 kWh/a Consumption (AEChood) Energy efficieency class A Fluid Dynamic Efficiency 30.1 (FDE) Fluid Dynamic Efficiency A class (FDEC)

Lighting Efficiency (LE) 31.1 lux/W

Lighting Efficiency Class A (LEC)

**Grease Filtering** 77.9 % Efficiency (GFE) **Grease Filtering** 

Efficiency Class (GFEC) Air flow at minumum 242 m<sup>3</sup>/h

speed (Qmin)

Air flow at maximum speed (Qmax)

Air flow at boost speed 697 m<sup>3</sup>/h

481 m<sup>3</sup>/h

(Qboost)

Airbourne acouistical A- 45 dBA

weighted sound Power **Emission at minimum** speed (SPEmin)

Airborne acoustical A-60 dBA weighted sound Power Emission at maximum speed (SPEmax)

Airbourne acoustical A- 67 dBA weighted sound power emission at boost speed

(SPEboost)

Time increase factor (F) **Energy Efficiency Index** 52.6 Measured air flow rate 369 m<sup>3</sup>/h

at best efficiency point

Measured air pressure 446 Pa

at best efficiency point

(Pbep)

Measured electric 152 W power input at best efficiency point (Wbep)

**Nominal Power** 5 W consumption of the light

system (WL)

Average illumination of 143 lux

the light on the cooking surface (Emiddle)

Sound power level at highest setting (Lwa)

60 dBA

1500 mm

#### **Electrical Connection**

**Electrical connection** 235 W

rating

220-240 V Voltage Frequency (Hz) 50-60 Hz

Power supply cable

length

Plug Not present

### Also available

**SMEG SPA** 30/11/2025



Alternative colours available

Stainless steel

Available colours

KSG9P4X

SMEG SPA 30/11/2025



# **Compatible Accessories**

#### FLT6

Round Charcoal filters (kit 2 pieces)





#### **KITALLFC**

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

SMEG SPA 30/11/2025



## Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Perimeter extraction panels: very efficient and aid noise reduction.



Intensive/turbo setting: when extra fast extraction is required.



Connection between hob and hood



**Dimmering Lights** 



Tunable white from warm to cold

SMEG SPA 30/11/2025