

# KSG9P4X



## Product family

Hood Type	Integrated hood
Design	Fully integrated
Extraction	Extraction
Electronic control	Yes
Perimeter extraction	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709319380
Hood width	90 cm
Aesthetic	Universale
Colour	Stainless steel
Finishing	Satin
Logo	Silk screen



## Controls

Control setting	Touch control back-lighted	Led color	White
	White		

## Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-vent 2.0	

## Technical Features



No. of lights	2	No. of filters	2
Light type	LED	Anti-grease filters	Aluminium
Light Power	2,3 W	Filter replacement indicator	Yes
Dimmer mode	Yes	Vent outlet	150 mm
Light color temperature range	2700 - 4000 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	730 m <sup>3</sup> /h	Minimum distance from ELECTRIC hob	650 mm
Motor power	230 W	Non return valve	Yes


	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	243	45
Speed 2	362	53
Speed 3	481	59
Intensive speed	697	67

## Performance / Energy Label

 A6		
<b>Annual Efficiency Consumption (AEchood)</b>	53 kWh/a	Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin)
<b>Energy efficiency class (EEC)</b>	A	Airborne acoustical A- 60 dBA weighted sound Power Emission at maximum speed (SPEmax)
<b>Fluid Dynamic Efficiency (FDE)</b>	30,1	Airbourne acoustical A- 67 dBA weighted sound power emission at boost speed (SPEboost)
<b>Fluid Dynamic Efficiency class (FDEC)</b>	A	Time increase factor (F) 0,9
<b>Lighting Efficiency (LE)</b>	31,1 lux/W	Energy Efficiency Index 52,6
<b>Lighting Efficiency Class (LEC)</b>	A	Measured air flow rate at best efficiency point (Qbep) 369 m³/h
<b>Grease Filtering Efficiency (GFE)</b>	77,9 %	Measured air pressure at best efficiency point (Pbep) 446 Pa
<b>Grease Filtering Efficiency Class (GFEC)</b>	C	Measured electric power input at best efficiency point (Wbep) 152 W
<b>Air flow at minimum speed (Qmin)</b>	242 m³/h	Nominal Power consumption of the light system (WL) 5 W
<b>Air flow at maximum speed (Qmax)</b>	481 m³/h	Average illumination of the light on the cooking surface (Emiddle) 143 lux
<b>Air flow at boost speed (Qboost)</b>	697 m³/h	Sound power level at highest setting (Lwa) 60 dBA

## Electrical Connection

<b>Electrical connection rating</b>	235 W	<b>Power supply cable length</b>	1500 mm
<b>Voltage</b>	220-240 V	<b>Plug</b>	Not present
<b>Frequency (Hz)</b>	50-60 Hz		



---

## Compatible Accessories

---

### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304. The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

## Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Energy efficiency class A



Warning light(s): to advise when filters need changing.



Perimeter extraction panels: very efficient and aid noise reduction.



Connection between hob and hood



Tunable white from warm to cold.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.



Dimmering Lights