

KSGAU6P4MB



Product family Hood

Hood Type Integrated hood Fully integrated Design Extraction Extraction **Electronic control** Yes

Perimeter extraction Yes

Material Stainless steel Type of steel Brushed

EAN code 8017709331474

Hood width 60 cm **Aesthetic** Universale Colour Matte black **Finishing** Matte black Silk screen Logo



Controls

Control setting Touch control back-lighted Led color White

White

Program / Functions

No. of speeds Intensive speed

24h air filter function

Time-setting options

Auto-vent 2.0









Technical Features











2700 - 4000 K

730 m³/h

230 W

No. of lights 2 Light type **LED Light Power** 2,3 W Dimmer mode

Light color temperature

range

Free outlet maximum

capacity

Motor power

Anti-grease filters Filter replacement indicator

No. of filters

Vent outlet Minimum distance from

GAS hob

Minimum distance from

ELECTRIC hob

650 mm

150 mm

650 mm

Aluminium

Yes

Non return valve Yes

SMEG SPA 2/12/2025



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	265	49
Speed 2	360	56
Speed 3	484	61
Intensive speed	660	67

Performance / Energy Label

B

Annual Efficiency 58 kWh/a Consumption (AEChood) Energy efficieency class B (EEC) Fluid Dynamic Efficiency 27,9 (FDE) Fluid Dynamic Efficiency B class (FDEC) Lighting Efficiency (LE) 39,3 lux/W Lighting Efficiency Class A (LEC) **Grease Filtering** 74,9 % Efficiency (GFE) **Grease Filtering** D Efficiency Class (GFEC) Air flow at minumum 265 m³/h speed (Qmin) Air flow at maximum 484 m³/h speed (Qmax) Air flow at boost speed 660 m³/h

Airbourne acouistical A- 49 dBA weighted sound Power **Emission at minimum** speed (SPEmin) Airborne acoustical A-62 dBA weighted sound Power Emission at maximum speed (SPEmax) Airbourne acoustical A- 67 dBA weighted sound power emission at boost speed (SPEboost) Time increase factor (F) 1,0 **Energy Efficiency Index** 58 Measured air flow rate 348 m³/h at best efficiency point Measured air pressure 433 Pa at best efficiency point (Pbep) Measured electric 150 W power input at best efficiency point (Wbep) **Nominal Power** 5 W consumption of the light system (WL) Average illumination of 181 lux the light on the cooking surface (Emiddle)

Electrical Connection

Electrical connection 235 W

rating

(Qboost)

Voltage 220-240 V Frequency (Hz) 50-60 Hz Power supply cable

Sound power level at

highest setting (Lwa)

length


Plug (I) Australia


62 dBA


1500 mm

SMEG SPA 2/12/2025









SMEG SPA 2/12/2025



Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



...



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Perimeter extraction panels: very efficient and aid noise reduction.



Intensive/turbo setting: when extra fast extraction is required.



...



...



SMEG SPA 2/12/2025