

KSGAU6P4MB



Product family

Hood Type	Integrated hood
Design	Fully integrated
Extraction	Extraction
Electronic control	Yes
Perimeter extraction	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709331474
Hood width	60 cm
Aesthetic	Universale
Colour	Matte black
Finishing	Matte black
Logo	Silk screen



Controls

Control setting	Touch control back-lighted	Led color	White
	White		

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-vent 2.0	

Technical Features



No. of lights	2	No. of filters	2
Light type	LED	Anti-grease filters	Aluminium
Light Power	2,3 W	Filter replacement indicator	Yes
Dimmer mode	Yes	Vent outlet	150 mm
Light color temperature range	2700 - 4000 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	730 m ³ /h	Minimum distance from ELECTRIC hob	650 mm
Motor power	230 W	Non return valve	Yes


	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	265	49
Speed 2	360	56
Speed 3	484	61
Intensive speed	660	67

Performance / Energy Label

 B	Annual Efficiency Consumption (AEchood)	58 kWh/a	Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin)	49 dBA
Energy efficiency class (EEC)	Energy efficiency class B		Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax)	62 dBA
Fluid Dynamic Efficiency (FDE)	Fluid Dynamic Efficiency 27,9		Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	67 dBA
Fluid Dynamic Efficiency class (FDEC)	B		Time increase factor (F)	1,0
Lighting Efficiency (LE)	39,3 lux/W		Energy Efficiency Index	58
Lighting Efficiency Class (LEC)	A		Measured air flow rate at best efficiency point (Qbep)	348 m³/h
Grease Filtering Efficiency (GFE)	74,9 %		Measured air pressure at best efficiency point (Pbep)	433 Pa
Grease Filtering Efficiency Class (GFEC)	D		Measured electric power input at best efficiency point (Wbep)	150 W
Air flow at minimum speed (Qmin)	265 m³/h		Nominal Power consumption of the light system (WL)	5 W
Air flow at maximum speed (Qmax)	484 m³/h		Average illumination of the light on the cooking surface (Emiddle)	181 lux
Air flow at boost speed (Qboost)	660 m³/h		Sound power level at highest setting (Lwa)	62 dBA

Electrical Connection

Electrical connection rating	235 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	(I) Australia
Frequency (Hz)	50-60 Hz		



Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Perimeter extraction panels: very efficient and aid noise reduction.



Dimmering Lights



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Connection between hob and hood



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.



Tunable white from warm to cold.