

KSGAU6P4X



Product family

Hood Type	Integrated hood
Design	Fully integrated
Extraction	Extraction
Electronic control	Yes
Perimeter extraction	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709328382
Hood width	60 cm
Aesthetic	Universale
Colour	Stainless steel
Finishing	Satin
Logo	Silk screen



Controls

Control setting	Touch control back-lighted	Led color	White
	White		

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-vent 2.0	

Technical Features



No. of lights	2	No. of filters	2
Light type	LED	Anti-grease filters	Aluminium
Light Power	2,3 W	Filter replacement indicator	Yes
Dimmer mode	Yes	Vent outlet	150 mm
Light color temperature range	2700 - 4000 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	730 m ³ /h	Minimum distance from ELECTRIC hob	650 mm
Motor power	230 W	Non return valve	Yes


	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	265	49
Speed 2	360	56
Speed 3	484	61
Intensive speed	660	67

Performance / Energy Label

	B	
Annual Efficiency Consumption (AEchood)	58 kWh/a	Airbourne acoustical A- weighted sound Power
Energy efficiency class (EEC)		Emission at minimum speed (SPEmin)
Fluid Dynamic Efficiency (FDE)	27,9	Airborne acoustical A- weighted sound Power
Fluid Dynamic Efficiency class (FDEC)	B	Emission at maximum speed (SPEmax)
Lighting Efficiency (LE)	39,3 lux/W	Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)
Lighting Efficiency Class (LEC)	A	
Grease Filtering Efficiency (GFE)	74,9 %	Time increase factor (F) 1,0
Grease Filtering Efficiency Class (GFEC)	D	Energy Efficiency Index 58
Air flow at minimum speed (Qmin)	265 m³/h	Measured air flow rate at best efficiency point (Qbep) 348 m³/h
Air flow at maximum speed (Qmax)	484 m³/h	Measured air pressure at best efficiency point (Pbep) 433 Pa
Air flow at boost speed (Qboost)	660 m³/h	Measured electric power input at best efficiency point (Wbep) 150 W
		Nominal Power consumption of the light system (WL) 5 W
		Average illumination of the light on the cooking surface (Emiddle) 181 lux
		Sound power level at highest setting (Lwa) 62 dBA

Electrical Connection

Electrical connection rating	235 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	(I) Australia
Frequency (Hz)	50-60 Hz		



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Perimeter extraction panels: very efficient and aid noise reduction.



Dimmering Lights



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Connection between hob and hood



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.



Tunable white from warm to cold.