

# KT110BLE

|                |                      |
|----------------|----------------------|
| Product family | Hood                 |
| Hood Type      | Decorative wall hood |
| Design         | Chimney              |
| Extraction     | Extraction           |
| Material       | Painted material     |
| Type of steel  | Brushed              |
| EAN code       | 8017709211691        |
| Hood width     | 110 cm               |
| Aesthetic      | Victoria             |
| Colour         | Black                |
| Finishing      | Glossy               |
| Logo           | Applied              |



## Controls

|                 |               |                 |              |
|-----------------|---------------|-----------------|--------------|
| Control setting | Control knobs | Control knobs   | Victoria     |
| No. of controls | 2             | Controls colour | Steel effect |

## Program / Functions

|                 |   |
|-----------------|---|
| No. of speeds   | 3   |
| Intensive speed |  |

## Technical Features

|  |   |                                    |           |
|--|---|------------------------------------|-----------|
|  |  |                                    |           |
| No. of lights  | 2   | No. of filters                     | 4         |
| Light type   | LED   | Anti-grease filters                | Aluminium |
| Light Power  | 1 W   | Vent outlet                        | 150 mm    |
| Light color temperature scale (K)  | 3000 K  | Minimum distance from GAS hob      | 750 mm    |
| Free outlet maximum capacity   | 820 m <sup>3</sup> /h   | Minimum distance from ELECTRIC hob | 650 mm    |
| Motor power  | 275 W   | Non return valve                   | Yes       |

|         | Extraction rate IEC 61591 [m <sup>3</sup> /h] | Noise level IEC 60704-2-13 [dBA] |
|---------|---|----------------------------------|
| Speed 1 | 326   | 49                               |
| Speed 2 | 439   | 57                               |

|                 |     |    |
|-----------------|-----|----|
| Speed 3         | 554 | 63 |
| Intensive speed | 784 | 71 |

## Performance / Energy Label



|  |                       |  |                       |
|--|-----------------------|--|-----------------------|
| Annual Efficiency Consumption (AEChood)  | 57 kWh/a              | Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) | 49 dBA                |
| Energy efficiency class (EEC)            | A                     | Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)  | 63 dBA                |
| Fluid Dynamic Efficiency (FDE)           | 31.1                  | Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) | 71 dBA                |
| Fluid Dynamic Efficiency class (FDEC)    | A                     | Time increase factor (F)   | 1.00                  |
| Lighting Efficiency (LE)                 | 83.2 lux/W            | Energy Efficiency Index  | 52.2                  |
| Lighting Efficiency Class (LEC)          | A                     | Measured air flow rate at best efficiency point (Qbep)                         | 413 m <sup>3</sup> /h |
| Grease Filtering Efficiency (GFE)        | 69.2 %                | Measured air pressure at best efficiency point (Pbep)                          | 456 Pa                |
| Grease Filtering Efficiency Class (GFEC) | D                     | Measured electric power input at best efficiency point (Wbep)                  | 168 W                 |
| Air flow at mininum speed (Qmin)         | 326 m <sup>3</sup> /h | Nominal Power consumption of the light system (WL)                             | 2 W                   |
| Air flow at maximum speed (Qmax)         | 554 m <sup>3</sup> /h | Average illumination of the light on the cooking surface (Emiddle)             | 183 lux               |
| Air flow at boost speed (Qboost)         | 784 m <sup>3</sup> /h | Sound power level at highest setting (Lwa)                                     | 63 dBA                |

## Electrical Connection

|                              |           |                           |             |
|------------------------------|-----------|---------------------------|-------------|
| Electrical connection rating | 278 W     | Power supply cable length | 1000 mm     |
| Voltage                      | 220-240 V | Plug                      | Not present |
| Frequency (Hz)               | 50-60 Hz  |                           |             |

## Also available

|                               |                               |                   |                            |
|-------------------------------|-------------------------------|-------------------|----------------------------|
| Alternative colours available | White, Stainless steel, Cream | Available colours | KT110BE-KTR110XE - KT110PE |
|-------------------------------|-------------------------------|-------------------|----------------------------|



---

## Compatible Accessories

---



### FLT6

Round Charcoal filters (kit 2 pieces)

KITCMNKT110N



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Energy efficiency class A**



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



**Intensive/turbo setting:** when extra fast extraction is required.