

# KT110BLE

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Painted material
Type of steel	Brushed
EAN code	8017709211691
Hood width	110 cm
Aesthetic	Victoria
Colour	Black
Finishing	Glossy
Logo	Applied



## Controls

Control setting	Control knobs	Control knobs	Victoria
No. of controls	2	Controls colour	Steel effect

## Program / Functions

No. of speeds	3
Intensive speed	

## Technical Features



No. of lights	2	No. of filters	4
Light type	LED	Anti-grease filters	Aluminium
Light Power	1 W	Vent outlet	150 mm
Light color temperature scale (K)	3000 K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	820 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	326	49
Speed 2	439	57

Speed 3	554	63
Intensive speed	784	71

## Performance / Energy Label




Annual Efficiency Consumption (AEChood)	57 kWh/a	Airbourne acoustical A- weighted sound Power	49 dBA
Energy efficiency class (EEC)	A	Emission at minimum speed (SPEmin)	
Fluid Dynamic Efficiency (FDE)	31,1	Airborne acoustical A- weighted sound Power	63 dBA
Fluid Dynamic Efficiency class (FDEC)	A	Emission at maximum speed (SPEmax)	
Lighting Efficiency (LE)	83,2 lux/W	Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	71 dBA
Lighting Efficiency Class (LEC)	A	Time increase factor (F)	1,00
Grease Filtering Efficiency (GFE)	69,2 %	Energy Efficiency Index	52,2
Grease Filtering Efficiency Class (GFEC)	D	Measured air flow rate at best efficiency point (Qbep)	413 m³/h
Air flow at minimum speed (Qmin)	326 m³/h	Measured air pressure at best efficiency point (Pbep)	456 Pa
Air flow at maximum speed (Qmax)	554 m³/h	Measured electric power input at best efficiency point (Wbep)	168 W
Air flow at boost speed (Qboost)	784 m³/h	Nominal Power consumption of the light system (WL)	2 W
		Average illumination of the light on the cooking surface (Emiddle)	183 lux
		Sound power level at highest setting (Lwa)	63 dBA

## Electrical Connection

Electrical connection rating	278 W	Power supply cable length	1000 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		

## Also available

Alternative colours available	White, Stainless steel, Cream	Available colours	KT110BE-KTR110XE - KT110PE
-------------------------------	-------------------------------	-------------------	----------------------------



## Compatible Accessories

---

### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

## Symbols glossary



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



**Energy efficiency class A**



**Intensive/turbo setting:** when extra fast extraction is required.