

# KT110PE

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Painted material
Type of steel	Brushed
EAN code	8017709211707
Hood width	110 cm
Aesthetic	Victoria
Colour	Cream
Finishing	Glossy
Logo	Applied



## Controls

Control setting	Control knobs	Control knobs	Victoria
No. of controls	2	Controls colour	Steel effect

## Program / Functions

No. of speeds	3
Intensive speed	

## Technical Features

			
No. of lights	2	No. of filters	4
Light type	LED	Anti-grease filters	Aluminium
Light Power	1 W	Vent outlet	150 mm
Light color temperature scale (K)	3000 K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	820 m <sup>3</sup> /h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	326	49
Speed 2	439	57

Speed 3	554	63
Intensive speed	784	71

## Performance / Energy Label




<b>Annual Efficiency Consumption (AEChood)</b>	57 kWh/a	<b>Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)</b>	49 dBA
<b>Energy efficiency class (EEC)</b>	A	<b>Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)</b>	63 dBA
<b>Fluid Dynamic Efficiency (FDE)</b>	31,1	<b>Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)</b>	71 dBA
<b>Fluid Dynamic Efficiency class (FDEC)</b>	A	<b>Energy Efficiency Index</b>	52,2
<b>Lighting Efficiency (LE)</b>	83,2 lux/W	<b>Measured air flow rate at best efficiency point (Qbep)</b>	413 m <sup>3</sup> /h
<b>Lighting Efficiency Class (LEC)</b>	A	<b>Measured air pressure at best efficiency point (Pbep)</b>	456 Pa
<b>Grease Filtering Efficiency (GFE)</b>	69,2 %	<b>Measured electric power input at best efficiency point (Wbep)</b>	168 W
<b>Grease Filtering Efficiency Class (GFEC)</b>	D	<b>Nominal Power consumption of the light system (WL)</b>	2 W
<b>Air flow at minumum speed (Qmin)</b>	326 m <sup>3</sup> /h	<b>Average illumination of the light on the cooking surface (Emiddle)</b>	183 lux
<b>Air flow at maximum speed (Qmax)</b>	554 m <sup>3</sup> /h	<b>Sound power level at highest setting (Lwa)</b>	63 dBA
<b>Air flow at boost speed (Qboost)</b>	784 m <sup>3</sup> /h		

## Electrical Connection

<b>Electrical connection rating</b>	278 W	<b>Power supply cable length</b>	1000 mm
<b>Voltage</b>	220-240 V	<b>Plug</b>	Not present
<b>Frequency (Hz)</b>	50-60 Hz		

## Also available

<b>Alternative colours available</b>	White, Black, Stainless steel	<b>Available colours</b>	KT110BE-KT110BLE - KTR110XE
--------------------------------------	-------------------------------	--------------------------	-----------------------------



---

## Compatible Accessories

---



**FLT6**

Round Charcoal filters (kit 2 pieces)

**KITCMNKT110P**



**KITALLFC**

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



A



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Intensive/turbo setting:** when extra fast extraction is required.