# KT110PE

| | |
|---|---|
| **Product family** | Hood |
| **Hood Type** | Decorative wall hood |
| **Design** | Chimney |
| **Extraction** | Extraction |
| **Material** | Painted material |
| **Type of steel** | Brushed |
| **EAN code** | 8017709211707 |
| **Hood width** | 110 cm |
| **Aesthetic** | Victoria |
| **Colour** | Cream |
| **Finishing** | Glossy |
| **Logo** | Applied |



## Controls

| | | | |
|---|---|---|---|
| **Control setting** | Control knobs | **Control knobs** | Victoria |
| **No. of controls** | 2 | **Controls colour** | Steel effect |

## Program / Functions

| | |
|---|---|
| **No. of speeds** | 3 |
| **Intensive speed** | BOOST |

## Technical Features

| | | | |
|---|---|---|---|
| **No. of lights** | 2 | **No. of filters** | 4 |
| **Light type** | LED | **Anti-grease filters** | Aluminium |
| **Light Power** | 1 W | **Vent outlet** | 150 mm |
| **Light color temperature (K)** | 3000 K | **Minimum distance from GAS hob** | 750 mm |
| **Free outlet maximum capacity** | 820 m³/h | **Minimum distance from ELECTRIC hob** | 650 mm |
| **Motor power** | 275 W | **Non return valve** | Yes |

| | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704-2-13 [dBA] |
|---|---|---|
| Speed 1 | 326 | 49 |
| Speed 2 | 439 | 57 |

| | | |
|---|---|---|
| Speed 3 | 554 | 63 |
| Intensive speed | 784 | 71 |

## Performance / Energy Label




| | |
|---|---|
| **Annual Efficiency Consumption (AEChood)** | 57 kWh/a |
| **Energy efficicency class (EEC)** | A |
| **Fluid Dynamic Efficiency (FDE)** | 31.1 |
| **Fluid Dynamic Efficiency class (FDEC)** | A |
| **Lighting Efficiency (LE)** | 83.2 lux/W |
| **Lighting Efficiency Class (LEC)** | A |
| **Grease Filtering Efficiency (GFE)** | 69.2 % |
| **Grease Filtering Efficiency Class (GFEC)** | D |
| **Air flow at minumum speed (Qmin)** | 326 m³/h |
| **Air flow at maximum speed (Qmax)** | 554 m³/h |
| **Air flow at boost speed (Qboost)** | 784 m³/h |
| **Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)** | 49 dBA |
| **Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)** | 63 dBA |
| **Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)** | 71 dBA |
| **Energy Efficiency Index** | 52.2 |
| **Measured air flow rate at best efficiency point (Qbep)** | 413 m³/h |
| **Measured air pressure at best efficiency point (Pbep)** | 456 Pa |
| **Measured electric power input at best efficiency point (Wbep)** | 168 W |
| **Nominal Power consumption of the light system (WL)** | 2 W |
| **Average illumination of the light on the cooking surface (Emiddle)** | 183 lux |
| **Sound power level at highest setting (Lwa)** | 63 dBA |

## Electrical Connection

| | |
|---|---|
| **Electrical connection rating** | 278 W |
| **Voltage** | 220-240 V |
| **Frequency (Hz)** | 50-60 Hz |
| **Power supply cable length** | 1000 mm |
| **Plug** | Not present |

## Also available

| | |
|---|---|
| **Alternative colours available** | White, Black, Stainless steel |
| **Available colours** | KT110BE-KT110BLE - KTR110XE |


190
278
532
1100
480
316
min.750 - max.1185

## Compatible Accessories



**FLT6**

Round Charcoal filters (kit 2 pieces)

**KITCMNKT110P**



**KITALLFC**

Universal Charcoal filter  Stainless Steel AISI 304  The filter can be washed in dishwasher 50 °C (water and suitable detergent)  and to dry it put in the oven 180°C 25 minutes

## Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.




Intensive/turbo setting: when extra fast extraction is required.