

KT90DGC

Product family

Hood Type Decorative wall hood

Hood

DesignChimneyExtractionExtractionMaterialPainted material

Type of steel Brushed

EAN code 8017709266721

Hood width 90 cm



Aesthetics

Aesthetic Victoria Decoration / Special Sicilian cart

Series Divina Cucina colour

Colour Decorated / Special Collaborations Smeg & Dolce&Gabbana

Finishing Glossy Logo Applied

Controls

Control settingControl knobsControl knobsVictoriaNo. of controls2Controls colourSteel effect

Programs / Functions main oven

No. of speeds 3
Intensive speed

Technical Features

-Ö-

No. of lights 2 No. of filters 3

Light typeLEDAnti-grease filtersStainless steelLight Power1 WVent outlet150 mmLight color temperature3000 °KMinimum distance from750 mm

scale (°K) GAS hob



Free outlet maximum

820 m³/h

Minimum distance from **ELECTRIC** hob

650 mm

capacity

Motor power

275 W

Non return valve

Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	334	49
Speed 2	439	57
Speed 3	567	61
Intensive speed	788	69

334 m³/h

567 m³/h

Performance / Energy Label

A †

Annual Efficiency 59 kWh/a

Consumption (AEChood)

Energy efficieency class A

(EEC)

Fluid Dynamic Efficiency 30

(FDE)

Fluid Dynamic Efficiency A

class (FDEC)

Lighting Efficiency (LE) 102.3 lux/W

Lighting Efficiency Class A

Grease Filtering 76.6 %

Efficiency (GFE)

Grease Filtering C

Efficiency Class (GFEC)

Air flow at minumum

speed (Qmin)

Air flow at maximum

speed (Qmax)

Air flow at boost speed 788 m³/h

(Qboost)

Airbourne acouistical A- 49 dBA

weighted sound Power **Emission at minimum**

speed (SPEmin)

Airborne acoustical A-61 dBA

weighted sound Power **Emission at maximum** speed (SPEmax)

Airbourne acoustical A- 69 dBA

weighted sound power emission at boost speed

(SPEboost)

Time increase factor (F) **Energy Efficiency Index** 52.4

Measured air flow rate 438 m³/h at best efficiency point

(Qbep)

Measured air pressure

at best efficiency point

(Pbep)

Measured electric 176 W

power input at best efficiency point (Wbep)

Nominal Power consumption of the light

system (WL)

Average illumination of

the light on the cooking surface (Emiddle)

Sound power level at highest setting (Lwa) 225 lux

2 W

434 Pa

61 dBA

Electrical Connection

Frequency (Hz) 50-60 Hz Plug Not present



Electrical connection rating

278 W

Power supply cable length

1000 mm

Voltage

220-240 V

Also available

Alternative colours availible

Caltagirone majolica

Available colours

KT90DGM



Not included accessories

FLT6

Round Charcoal filters (kit 2 pieces)





KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



Symbols glossary (TT)





Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Intensive/turbo setting: when extra fast extraction is required.