

KT90DGM

Product family Hood

Hood Type Chimney Cooker Hoods

Design Chimney

Extraction Ducted out or re-circulation possible

Material Painted material

Type of steel Brushed

EAN code 8017709266714

Hood width 90 cm Aesthetics Victoria

Colour Decorated / Special

Decoration / Special colour Maiolica
Finishing Gloss

Series Divina Cucina

Collaborations Smeg & Dolce&Gabbana

Logo Applied



Controls

Control settingControl knobsControl knobsVictoriaNo. of controls2Controls colourSteel effect

Program / Functions

No. of speeds Intensive speed

3

Technical Features





No. of lights 2 No. of filters 3

Light typeLEDAnti-grease filtersStainless steelLight power1 WVent outlet150 mmLight colour3000 KMinimum distance from
750 mm

temperature scale (K) GAS hob

Free outlet maximum 820 m³/h Minimum distance from 650 mm

capacity ELECTRIC hob

Motor power 275 W Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	334	49
Speed 2	439	57

SMEG SPA 03/12/2025



Speed 3	567	61
Intensive speed	788	69

Performance / Energy Label

_	tr
	Ť

Annual Efficiency 59 kWh/year Airbourne acouistical A- 49 dBA weighted sound Power Consumption (AEChood) **Emission at minimum** Energy efficiency class (A speed (SPEmin) EEC) Airborne acoustical A-61 dBA Fluid Dynamic Efficiency 30 weighted sound Power (FDE) **Emission at maximum** Fluid Dynamic Efficiency A speed (SPEmax) class (FDEC) Airbourne acoustical A- 69 dBA Lighting Efficiency (LE) 102,3 lux/W weighted sound power Lighting Efficiency Class A emission at boost speed (LEC) (SPEboost) **Grease Filtering** 76.6 % Time increase factor (F) Efficiency (GFE) **Energy Efficiency Index** 52,4 **Grease Filtering** per first cavity Efficiency Class (GFEC) Measured air flow rate 438 m³/h Air flow at minumum 334 m³/h at best efficiency point speed (Qmin) (Qbep) Maximum extraction 567 m³/h Measured air pressure 434 Pa at best efficiency point Intensive extraction rate 788 m³/h (Qbep) Measured electric 176 W power input at best efficiency point (Wbep) Normal Power of the 2 W light system (WI) Average illumination of 225 lux

Electrical Connection

Nominal power 278 W Frequency (Hz) 50-60 Hz Voltage 220-240 V Power supply cable 1000 mm length

Also available

Alternative colours Sicilian Cart Available colours KT90DGC available

SMEG SPA 03/12/2025

the light on the cooking surface (Emiddle) Sound power level at

highest setting (Lwa)

61 dBA



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)





KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

SMEG SPA 03/12/2025



Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



A: Product drying performance, measured from A+++ to D / G depending on the product family



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.

SMEG SPA 03/12/2025