

KT90DGME

Product family

Hood
Chimney Cooker Hoods

Design
Chimney

Extraction
Ducted out or re-circulation possible

Material
Painted material

Type of steel
Brushed

EAN code
8017709334062

Hood width
90 cm

Aesthetics
Victoria

Colour
Decorated / Special

Decoration / Special colour
Blu Mediterraneo

Finishing
Gloss

Series
Divina Cucina

Collaborations
Smeg & Dolce&Gabbana

Logo
Applied



Controls

Control setting
Control knobs

No. of controls
2

Control knobs
Controls colour

Victoria
Steel effect

Program / Functions

No. of speeds
3

Intensive speed


Technical Features



No. of lights
2

Light type
LED

Light power
1 W

Light colour
3000 K

temperature scale (K)
6500 K

Free outlet maximum
capacity
820 m³/h

Motor power
275 W

No. of filters
3

Anti-grease filters
Stainless steel

Vent outlet
150 mm

Minimum distance from
GAS hob
750 mm

Minimum distance from
ELECTRIC hob
650 mm

Non return valve
Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	334	49
Speed 2	439	57

Speed 3	567	61
Intensive speed	788	69

Performance / Energy Label




Annual Efficiency Consumption (AEChood)	59 kWh/year	Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin)	49 dBA
Energy efficiency class (A EEC)		Emission at maximum speed (SPEmax)	61 dBA
Fluid Dynamic Efficiency (FDE)	30	Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	69 dBA
Fluid Dynamic Efficiency class (FDEC)	A	Time increase factor (F)	1,00
Lighting Efficiency (LE)	102,3 lux/W	Energy Efficiency Index per first cavity	52,4
Lighting Efficiency Class (LEC)	A	Measured air flow rate at best efficiency point (Qbep)	438 m³/h
Grease Filtering Efficiency (GFE)	76,6 %	Measured air pressure at best efficiency point (Qbep)	434 Pa
Grease Filtering Efficiency Class (GFEC)	C	Measured electric power input at best efficiency point (Wbep)	176 W
Air flow at minimum speed (Qmin)	334 m³/h	Normal Power of the light system (WI)	2 W
Maximum extraction rate	567 m³/h	Average illumination of the light on the cooking surface (Emiddle)	225 lux
Intensive extraction rate	788 m³/h	Sound power level at highest setting (Lwa)	61 dBA

Electrical Connection

Nominal power	278 W	Power supply cable length	1000 mm
Voltage	220-240 V	Plug	No
Frequency (Hz)	50-60 Hz		

Also available

Alternative colours available	Sicilian Cart	Available colours	KT90DGC
--------------------------------------	---------------	--------------------------	---------



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary

 A: Product drying performance, measured from A+++ to D / G depending on the product family



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.

 Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.