

KT90DGME

Product family Hood

Hood Type Decorative wall hood

Design Chimney
Extraction Extraction
Material Painted material

Type of steel Brushed

EAN code 8017709334062

Hood width 90 cm



Aesthetics

Aesthetic Victoria Decoration / Special Blu Mediterraneo

Series Divina Cucina colour

Colour Decorated / Special Collaborations Smeg & Dolce&Gabbana

Finishing Glossy Logo Applied

Controls

Control settingControl knobsControl knobsVictoriaNo. of controls2Controls colourSteel effect

Technical Features

No. of lights 2 No. of filters 3

Light typeLEDAnti-grease filtersStainless steelLight Power1 WVent outlet150 mmLight color temperature3000 °KMinimum distance from750 mm

scale (°K) GAS hob

Free outlet maximum 820 m³/h Minimum distance from 650 mm

capacity ELECTRIC hob

Motor power 275 W Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	334	49



Speed 2	439	57
Speed 3	567	61
Intensive speed	788	69

Performance / Energy Label

	tr
<	Ť
	D

Annual Efficiency 59 kWh/a Airbourne acouistical A- 49 dBA weighted sound Power Consumption (AEChood) Emission at minimum Energy efficieency class A speed (SPEmin) (EEC) Airborne acoustical A-61 dBA Fluid Dynamic Efficiency 30 weighted sound Power (FDE) Emission at maximum Fluid Dynamic Efficiency A speed (SPEmax) class (FDEC) Airbourne acoustical A- 69 dBA Lighting Efficiency (LE) 102.3 lux/W weighted sound power Lighting Efficiency Class A emission at boost speed (LEC) (SPEboost) **Grease Filtering** 76.6 % Time increase factor (F) Efficiency (GFE) **Energy Efficiency Index** 52.4 **Grease Filtering** C Measured air flow rate 438 m³/h Efficiency Class (GFEC) at best efficiency point Air flow at minumum 334 m³/h (Qbep) speed (Qmin) Measured air pressure 434 Pa Air flow at maximum 567 m³/h at best efficiency point speed (Qmax) (Pbep) Air flow at boost speed 788 m³/h Measured electric 176 W (Qboost) power input at best efficiency point (Wbep) **Nominal Power** 2 W consumption of the light system (WL) Average illumination of

surface (Emiddle) Sound power level at

220-240 V

highest setting (Lwa)

the light on the cooking

61 dBA

Electrical Connection

Plug Not present Frequency (Hz) 50-60 Hz
Electrical connection 278 W Power supply cable 1000 mm length

Also available

Voltage

Alternative colours Sicilian Cart Available colours KT90DGC availible





Not included accessories

FLT6

Round Charcoal filters (kit 2 pieces)





KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



Symbols glossary (TT)



<u>`Ö</u>-



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Intensive/turbo setting: when extra fast extraction is required.

Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.