

KV194G



Product family Hood

Hood Type Decorative wall hood

DesignAngledExtractionExtractionElectronic controlYesPerimeter extractionYesMaterialGlass

EAN code 8017709327897

Hood width 90 cm Aesthetic Linea

Colour Neptune Grey

Finishing Glass
Glass Type Black
Serigraphy colour Grey
Logo Silk screen



Controls

Control setting Touch control back-lighted Led color White

White

Program / Functions

No. of speeds
Intensive speed

. **.**

Time-setting options

Auto-vent 2.0

Technical Features

24h air filter function



No. of lights2Anti-grease filtersStainless steelLight typeLEDCharcoal filters includedYes

Light Power 2,1 W Filter replacement Yes indicator

Light color temperature 2700 - 4000 K Vent outlet 150 mm

range Minimum distance from 650 mm Free outlet maximum 820 m³/h GAS hob

capacity Minimum distance from 450 mm
Motor power 275 W ELECTRIC hob



No. of filters 2 Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	277	50
Speed 2	406	63
Speed 3	636	70
Intensive speed	782	72

Performance / Energy Label

A t

Annual Efficiency 41 kWh/a Airbourne acouistical A- 50 dBA Consumption (AEChood) weighted sound Power

Consumption (AEChood) weighted sound Power Energy efficiency class A+ Emission at minimum

(EEC) speed (SPEmin)

Fluid Dynamic Efficiency 36,2

Airborne acoustical A- 71 dBA

(FDE) weighted sound Power
Fluid Dynamic Efficiency A Emission at maximum
speed (SPEmax)

class (FDEC)

Linking Efficiency (LE) 24.0 km/M

Airbourne acoustical A- 72 dBA

Lighting Efficiency (LE) 34,8 lux/W weighted sound power emission at boost speed

(LEC) (SPEboost)

Grease Filtering 64,3 % Time increase factor (F)

Grease Filtering E

Energy Efficiency Index 41,2

Measured air flow rate 403 m³/h

Air flow at minumum 277 m³/h

(Oben)

speed (Qmin)

(Qbep)

Measured air pressure 479 Pa

Air flow at maximum 636 m³/h at best efficiency point (Pbep)

Air flow at boost speed 782 m³/h Measured electric 148 W (Qboost) power input at best

efficiency point (Wbep)

Nominal Power 5 W

Nominal Power 5 W consumption of the light system (WL)

Average illumination of 139 lux

the light on the cooking surface (Emiddle)

Sound power level at 71 dBA highest setting (Lwa)

Electrical Connection

Electrical connection 279 W Power supply cable 1500 mm

rating length

Voltage 220-240 V Plug Not present Frequency (Hz) 50-60 Hz




Also available


Alternative colours available


Black


Available colours

KV194B3











Compatible Accessories



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



KITCMNKVX

Chimney Extension in Stainless Steel for hood KV*series Dimensions 300x200x850 mm



KITCMNKVMB

Chimney Extension in Stainless Steel for hood KV*series 300 mm*200 mm + 500/850 mm



KITFCKV1

Kit 2 pcs Charcoal Filter for Hood KV1*series. Dishwasher-safe. Size 320x80 mm and 280 x280 mm.



Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Perimeter extraction panels: very efficient and aid noise reduction.



Intensive/turbo setting: when extra fast extraction is required.



Connection between hob and hood



Dimmering Lights



Tunable white from warm to cold