KV394MB

Product family	Hood
Hood Type	Decorative wall hood
Design	Angled
Extraction	Extraction
Electronic control	Yes
Perimeter extraction	Yes
Material	Glass
EAN code	8017709319816
Hood width	90 cm
Aesthetic	Universale
Colour	Matte black
Finishing	Matte
Glass Type	Black
Serigraphy colour	Grey
Logo	Silk screen



Controls

Control setting	Touch control back-lighted White	**Led color**	White

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-vent 2.0	

Technical Features

No. of lights	2	**No. of filters**	2
Light type	LED	**Anti-grease filters**	Aluminium
Light Power	1,1 W	**Filter replacement indicator**	Yes
Dimmer mode	Yes	**Vent outlet**	150 mm
Light color temperature scale (K)	4000 K	**Minimum distance from GAS hob**	650 mm
Free outlet maximum capacity	730 m³/h	**Minimum distance from ELECTRIC hob**	450 mm

Motor power	230 W	**Non return valve**	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	285	47
Speed 2	374	54
Speed 3	493	60
Intensive speed	729	69

Accessories Included



Charcoal filters included Yes


Performance / Energy Label





Annual Efficiency Consumption (AEChood)	53 kWh/a	**Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)**	47 dBA
Energy efficicency class (EEC)	A	**Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)**	61 dBA
Fluid Dynamic Efficiency (FDE)	31,4	**Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)**	69 dBA
Fluid Dynamic Efficiency class (FDEC)	A	**Time increase factor (F)**	0,9
Lighting Efficiency (LE)	118,5 lux/W	**Energy Efficiency Index**	51,6
Lighting Efficiency Class (LEC)	A	**Measured air flow rate at best efficiency point (Qbep)**	397 m³/h
Grease Filtering Efficiency (GFE)	73,8 %	**Measured air pressure at best efficiency point (Pbep)**	443 Pa
Grease Filtering Efficiency Class (GFEC)	D	**Measured electric power input at best efficiency point (Wbep)**	155 W
Air flow at minumum speed (Qmin)	285 m³/h	**Nominal Power consumption of the light system (WL)**	2 W
Air flow at maximum speed (Qmax)	493 m³/h	**Average illumination of the light on the cooking surface (Emiddle)**	237 lux
Air flow at boost speed (Qboost)	729 m³/h	**Sound power level at highest setting (Lwa)**	61 dBA


Electrical Connection

Electrical connection rating	232 W	**Power supply cable length**	1500 mm
Voltage	220-240 V	**Plug**	No
Frequency (Hz)	50-60 Hz		









Compatible Accessories



FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



KITCMNKVMB

Chimney Extension in Stainless Steel for hood KV*series 300 mm*200 mm + 500/850 mm



KITCMNKVX

Chimney Extension in Stainless Steel for hood KV*series

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Connection between hob and hood



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Dimmering Lights



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



A: Product drying performance, measured from A+++ to D / G depending on the product family



Warning light(s): to advise when filters need changing.



Perimeter extraction panels: very efficient and aid noise reduction.