

# KV394MB



**Product family** Hood

Decorative wall hood **Hood Type** 

Design Angled Extraction Extraction **Electronic control** Yes Yes Perimeter extraction Material Glass

EAN code 8017709319816

Hood width 90 cm **Aesthetic** Universale Colour Matt Black **Finishing** Matt Glass Type Black Serigraphy colour Grey Logo Silk screen



#### **Controls**

Control setting Touch control back-lighted Led color White

White

## **Program / Functions**

No. of speeds Intensive speed

Time-setting options

Auto-vent 2.0

4000 K

730 m<sup>3</sup>/h

### **Technical Features**

24h air filter function









No. of lights 2 Light type **LED Light Power** 1,1 W Dimmer mode

Light color temperature

scale (K)

Free outlet maximum

capacity

Anti-grease filters Charcoal filters included Yes

Aluminium

Yes

Filter replacement indicator

150 mm

Minimum distance from

650 mm 450 mm

GAS hob

Vent outlet

Minimum distance from

**ELECTRIC hob** 



Motor power 230 W Non return valve Yes No. of filters 2

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	285	47
Speed 2	374	54
Speed 3	493	60
Intensive speed	729	69

### Performance / Energy Label

A †

Annual Efficiency 53 kWh/a Airbourne acouistical A- 47 dBA
Consumption (AEChood) weighted sound Power

Energy efficiency class A Emission at minimum (FEC) speed (SPEmin)

Fluid Dynamic Efficiency 31,4 Airborne acoustical A- 61 dBA

(FDE)

Fluid Dynamic Efficiency A

class (FDEC)

weighted sound Power
Emission at maximum
speed (SPEmax)

Lighting Efficiency (LE) 118,5 lux/W

Airbourne acoustical A- 69 dBA

Lighting Efficiency Class A weighted sound power emission at boost speed

(LEC) (SPEboost)
Grease Filtering 73,8 %
Time increase

Grease Filtering 73,8 % Time increase factor (F) 0,9

Efficiency (GFE) Energy Efficiency Index 51,

Measured air flow rate 397

Efficiency Class (GFEC)

Measured air flow rate 397 m³/h
at hest efficiency point

Air flow at minumum 285 m³/h (Qbep)
speed (Qmin)

Air flow at maximum 493 m³/h Measured air pressure 443 Pa at best efficiency point

speed (Qmax) (Pbep)
Air flow at boost speed 729 m³/h Measured electric 155 W

(Qboost)

power input at best
efficiency point (Wbep)
Nominal Power 2 W

consumption of the light system (WL)

Average illumination of 237 lux the light on the cooking

surface (Emiddle)
Sound power level at 61 dBA


highest setting (Lwa)


# Electrical Connection


Electrical connection 232 W Power supply cable 1500 mm rating length


Voltage 220-240 V Plug Not present Frequency (Hz) 50-60 Hz













# **Compatible Accessories**

#### FLT6

Round Charcoal filters (kit 2 pieces)



#### **KITCMNKVMB**

Chimney Extension in Stainless Steel for hood KV\*series 300 mm\*200 mm + 500/850 mm



#### **KITALLFC**

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



Chimney Extension in Stainless Steel for hood KV\*series Dimensions 300x200x850 mm



## Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Energy efficiency class A



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Perimeter extraction panels: very efficient and aid noise reduction.



Intensive/turbo setting: when extra fast extraction is required.



Connection between hob and hood



**Dimmering Lights**