

KV394N



Product family Hood

Decorative wall hood **Hood Type**

Design Angled Extraction Extraction **Electronic control** Yes Yes Perimeter extraction Material Glass

EAN code 8017709305758

Hood width 90 cm **Aesthetic** Universale Colour Black **Finishing** Glass Glass Type Black Serigraphy colour Grey Logo Silk screen



Controls

Control setting Touch control back-lighted Led color White

White

Program / Functions

No. of speeds Intensive speed

24h air filter function

Time-setting options

Auto-vent 2.0







Technical Features













730 m³/h

No. of lights 2 Light type **LED Light Power** 1,1 W Dimmer mode 4000 K

Light color temperature

scale (K)

Free outlet maximum

capacity

Anti-grease filters

Charcoal filters included Yes Filter replacement Yes

indicator

Vent outlet Minimum distance from

GAS hob

Minimum distance from

ELECTRIC hob

450 mm

150 mm

650 mm

Aluminium

SMEG SPA 27/11/2025



Motor power 230 W Non return valve Yes No. of filters 2

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	285	47
Speed 2	374	54
Speed 3	493	60
Intensive speed	729	69

Performance / Energy Label

A †

Annual Efficiency 53 kWh/a Airbourne acouistical A- 47 dBA
Consumption (AEChood) weighted sound Power

Energy efficiency class A Emission at minimum (FFC) speed (SPEmin)

Fluid Dynamic Efficiency 31,4 Airborne acoustical A- 61 dBA

(FDE) weighted sound Power
Fluid Dynamic Efficiency A
class (FDEC) weighted sound Power
Emission at maximum
speed (SPEmax)

Lighting Efficiency (LE) 118,5 lux/W Airbourne acoustical A- 69 dBA weighted sound power

Lighting Efficiency Class A emission at boost speed (LEC) (SPEheast)

Grease Filtering 73,8 % Time increase

Efficiency (GFE)

Grease Filtering

73,8 %

Time increase factor (F) 0,9

Energy Efficiency Index 51,6

Magazined air flow rate 307

Efficiency Class (GFEC)

Measured air flow rate 397 m³/h
at best efficiency point

Air flow at minumum 285 m³/h (Qbep)
speed (Qmin)

Air flow at maximum 493 m³/h speed (Qmax)

Measured air pressure 443 Pa at best efficiency point

Air flow at boost speed 729 m³/h (Pbep)

Measured electric 155 W

(Qboost) power input at best efficiency point (Wbep)

Nominal Power 2 W consumption of the light

system (WL)

Average illumination of 237 lux the light on the cooking

surface (Emiddle)

Sound power level at 61 dBA highest setting (Lwa)

Electrical Connection

Electrical connection 232 W Power supply cable 1500 mm


 rating
 length


 Voltage
 220-240 V
 Plug
 Not present


 Frequency (Hz)
 50-60 Hz
 Not present


SMEG SPA 27/11/2025











SMEG SPA 27/11/2025



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)



KITCMNKVMB

Chimney Extension in Stainless Steel for hood KV*series 300 mm*200 mm + 500/850 mm



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

KITCMNKVX

Chimney Extension in Stainless Steel for hood KV*series Dimensions 300x200x850 mm





Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Perimeter extraction panels: very efficient and aid noise reduction.



Intensive/turbo setting: when extra fast extraction is required.



Connection between hob and hood



Dimmering Lights

SMEG SPA 27/11/2025