

KV694R



Product family

Decorative wall hood **Hood Type**

Hood

Design Angled Extraction Extraction

Electronic control Yes Perimeter extraction Yes Material Glass

EAN code 8017709305789

Hood width 90 cm



Black

Grey

Stainless steel

Aesthetics

Dolce Stil Novo Glass Type **Aesthetic** Serigraphy colour Colour Black

Finishing Copper Logo Silk screen

Controls

Control setting Touch control back-lighted Led color White

White

Programs / Functions

No. of speeds Intensive speed

24h air filter function

Time-setting options

Auto-vent 2.0









Technical Features















No. of lights 2 Light type **LED Light Power** 2.1 W Anti-grease filters

Charcoal filters included Yes



Dimmer mode Filter replacement Yes Yes indicator Light color temperature 2700° - 4000° °K Vent outlet 150 mm range Minimum distance from 650 mm Free outlet maximum 820 m³/h **GAS** hob capacity Minimum distance from 450 mm Motor power 275 W **ELECTRIC hob** No. of filters 2 Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2- 13 [dB(A)]
Speed 1	265	47
Speed 2	391	55
Speed 3	621	66
Intensive speed	777	70

Performance / Energy Label

A*

Annual Efficiency Consumption (AEChood) Energy efficieency class (EEC)	42 kWh/a A+	Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax)	67 dB(A)
Fluid Dynamic Efficiency (FDE) Fluid Dynamic Efficiency		Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	70 dB(A)
class (FDEC) Lighting Efficiency (LE) Lighting Efficiency Class		Power Consumption in Off mode (Po) Power consumption in	0,49 W 0,99 W
(LEC) Grease Filtering Efficiency (GFE)	64,2 %	stand-by mode (Ps) Time increase factor (F)	0,99 W
Grease Filtering Efficiency Class (GFEC)	Е	Energy Efficiency Index Measured air flow rate	41,3 400 m³/h
Air flow at minumum speed (Qmin)	265 m³/h	at best efficiency point (Qbep) Measured air pressure	485 Pa
Air flow at maximum speed (Qmax)	621 m³/h	at best efficiency point (Pbep)	405 Fu
Air flow at boost speed (Qboost)	777 m³/h	Measured electric power input at best	151 W
Airbourne acouistical A- weighted sound Power Emission at minimum speed (SPEmin)	47 dB(A)	efficiency point (Wbep) Nominal Power consumption of the light system (WL)	4 W
		Average illumination of the light on the cooking surface (Emiddle)	142 lux
		Sound power level at highest setting (Lwa)	67 dB(A)



Electrical Connection

Electrical connection


279 W


rating Voltage


220-240 V


Frequency (Hz)
Power supply cable
length

50-60 Hz 1500 mm











Not included accessories

KITFCKV6



Kit 3 pcs of charcoal filter for vertical hood KV6* series. Dishwasher-safe. Size 320x80mm and 2 pcs 210x280 mm




KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



KITCMNKVX

Chimney Extension in Stainless Steel for hood KV*series 300 mm*200 mm + 500/850 mm



Chimney Extension in Stainless Steel for hood KV*series 300 mm*200 mm + 500/850 mm



Symbols glossary (TT)



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Connection between hob and hood



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Perimeter extraction panels: very efficient and aid noise reduction.



Intensive/turbo setting: when extra fast extraction is required.



Dimmering Lights



Tunable white from warm to cold