

KV694R



Product family Hood

Decorative wall hood **Hood Type**

Design Angled Extraction Extraction **Electronic control** Yes Perimeter extraction Yes Material Glass

EAN code 8017709305789

Hood width 90 cm

Aesthetic Dolce Stil Novo

Colour Black **Finishing** Copper Glass Type Black Serigraphy colour Grey Logo Silk screen



Controls

Control setting Touch control back-lighted Led color White

White

Program / Functions

No. of speeds Intensive speed

Time-setting options

Auto-vent 2.0

Technical Features







24h air filter function







No. of lights 2 Light type LED **Light Power** 2,1 W Dimmer mode

Light color temperature

range

Free outlet maximum

capacity

Motor power



2700 - 4000 K

820 m³/h

275 W

Anti-grease filters

Charcoal filters included Yes

Filter replacement indicator

Vent outlet Minimum distance from

GAS hob

Minimum distance from

ELECTRIC hob

Stainless steel

Yes

150 mm 650 mm

450 mm

SMEG SPA 12/27/2025



No. of filters 2 Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	265	47
Speed 2	391	55
Speed 3	621	66
Intensive speed	777	70

Performance / Energy Label

A* #

Annual Efficiency Airbourne acouistical A- 47 dBA 42 kWh/a

Consumption (AEChood) weighted sound Power **Emission at minimum** Energy efficieency class A+

speed (SPEmin) (EEC)

Airborne acoustical A-67 dBA Fluid Dynamic Efficiency 35,6 weighted sound Power

Emission at maximum Fluid Dynamic Efficiency A speed (SPEmax) class (FDEC)

Airbourne acoustical A- 70 dBA Lighting Efficiency (LE) 35,5 lux/W

weighted sound power Lighting Efficiency Class A emission at boost speed

(LEC) (SPEboost) **Grease Filtering** 64.2 %

Efficiency (GFE)

Energy Efficiency Index Grease Filtering Ε Measured air flow rate Efficiency Class (GFEC)

400 m³/h at best efficiency point Air flow at minumum 265 m³/h

(Qbep) speed (Qmin) Measured air pressure 485 Pa Air flow at maximum 621 m³/h

at best efficiency point speed (Qmax) (Pbep)

Air flow at boost speed 777 m³/h Measured electric 151 W (Qboost) power input at best efficiency point (Wbep)

Nominal Power 4 W consumption of the light

system (WL) Average illumination of 142 lux

Time increase factor (F)

the light on the cooking surface (Emiddle)

Sound power level at 67 dBA highest setting (Lwa)

Electrical Connection

Frequency (Hz)


Electrical connection 279 W Power supply cable 1500 mm


rating length Voltage 220-240 V Plug Not present


50-60 Hz


SMEG SPA 12/27/2025











SMEG SPA 12/27/2025



Compatible Accessories



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



KITCMNKVX

Chimney Extension in Stainless Steel for hood KV*series Dimensions 300x200x850 mm



KITCMNKVMB

Chimney Extension in Stainless Steel for hood KV*series 300 mm*200 mm + 500/850 mm



KITFCKV6

Kit 3 pcs of charcoal filter for vertical hood KV6* series. Dishwasher-safe. Size 320x80mm and 2 pcs 210x280 mm

SMEG SPA 12/27/2025



Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Connection between hob and hood



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Dimmering Lights



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Perimeter extraction panels: very efficient and aid noise reduction.



Tunable white from warm to cold



Intensive/turbo setting: when extra fast extraction is required.

SMEG SPA 12/27/2025