
KV694T

Product family	Hood
Hood Type	Chimney Cooker Hoods
Design	Angled
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Perimeter extraction	Yes
Material	Glass
EAN code	8017709367541
Hood width	90 cm
Aesthetics	Dolce Stil Novo
Colour	Black
Components finishing	Titanium
Glass Type	Black
Serigraphy colour	Grey
Logo	Silk screen



Controls

Control setting	Touch control back-lighted White	**Led colour**	White

Program / Functions

No. of speeds	3
Intensive speed	BOOST
24h air filter function	24
Time-setting options	
Auto-Vent 2.0	

Technical Features

No. of lights	2	**No. of filters**	2
Light type	LED	**Anti-grease filters**	Stainless steel
Light power	2,1 W	**Filter replacement indicator**	Yes
Dimmer mode	Yes	**Vent outlet**	150 mm
Light colour temperature range	2700 - 4000 K	**Minimum distance from GAS hob**	650 mm
Free outlet maximum capacity	820 m³/h	**Minimum distance from ELECTRIC hob**	450 mm
Motor power	275 W		

Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	265	47
Speed 2	391	55
Speed 3	621	66
Intensive speed	777	70

Accessories Included



Charcoal filters included	Yes

Performance / Energy Label





Annual Efficiency Consumption (AEChood)	42 kWh/year
Energy efficiency class (EEC)	A+
Fluid Dynamic Efficiency (FDE)	35,6
Fluid Dynamic Efficiency class (FDEC)	A
Lighting Efficiency (LE)	35,5 lux/W
Lighting Efficiency Class (LEC)	A
Grease Filtering Efficiency (GFE)	64,2 %
Grease Filtering Efficiency Class (GFEC)	E
Air flow at minumum speed (Qmin)	265 m³/h
Maximum extraction rate	621 m³/h
Intensive extraction rate	777 m³/h


Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)	47 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	67 dBA
Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)	70 dBA
Time increase factor (F)	0,7
Energy Efficiency Index per first cavity	41,3
Measured air flow rate at best efficiency point (Qbep)	400 m³/h
Measured air pressure at best efficiency point (Qbep)	485 Pa
Measured electric power input at best efficiency point (Wbep)	151 W
Normal Power of the light system (Wl)	4 W
Average illumination of the light on the cooking surface (Emiddle)	142 lux
Sound power level at highest setting (Lwa)	67 dBA


Electrical Connection

Voltage	220-240 V	**Power supply cable length**	1500 mm
Frequency (Hz)	50-60 Hz	**Plug**	No









Compatible Accessories



KITFCKV6

Kit 3 pcs of charcoal filter for vertical hood KV6* series

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.



Dimmering Lights



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Perimeter extraction panels: very efficient and aid noise reduction.



Connection between hob and hood



Tunable white from warm to cold.