

LD862-2

Sink material Stainless steel Welded sink Type

No. of bowls 2

EAN code 8017709198480



Aesthetics



Universale Building in type **Aesthetic** Ultra-low profile Series Mira Logo **Embossed** Colour Stainless steel Tap hole / precut tap 1 Tap hole

hole **Finishing** Brushed

	Bowl type RH	Bowl thickness (mm)	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Minimum radius	1	340 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"
LH Bowl	Minimum radius	1	340 x 400 x 200	200	15		Wall position	3.5"

Technical Features



0.7 mm Frame thickness Tap hole 1

Frame depth (mm) 14 Tap hole diameter 35 mm Dimensions of the 215x860x500 mm Dividing wall width 75 mm

product (mm) Gasket type Sealing paste

Cutout dimension 840 x 480 mm No. of clips 10

topmount (mm) Type of clips Standard

Undermount cutout

radius

5 mm




Height from kitchen top 6 mm Base unit size 90 cm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket





Compatible Accessories



DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



STABMIX

Tap stabiliser



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24.5



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Benefit (TT)

Two bowls

Two bowls for greater versatility and dual functionality

Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area