

LFT34RS

Sink material Stainless steel Welded bowl Type

No. of bowls 1

EAN code 8017709210328



Aesthetics

Aesthetic Universale Building in type Flush fitted, Flat Colour Stainless steel Logo **Embossed Finishing** Brushed Tap hole / precut tap 2 Tapholes hole

Series Mira

| _ | Bowl type | Bowl dimensions, WxDxH (mm) | Bowl depth (mm) | Radius corner bowl | Overflow | Strainer position | Strainer dimension |
|------|-------------------|--------------------------------|-----------------|-----------------------|----------------------|----------------------|-----------------------|
| Bowl | Minimum radius | 340 x 400 x 200 | 200 | 15 | Yes, flush fitted | Wall position | 3.5" |

Technical Features



Dimensions of the 200x402x510 mm product (mm)

Cutout dimension 370 x 490 mm

topmount (mm)

Height from kitchen top 1 mm Base unit size 45 cm Tap hole 2


Tap hole diameter 35 mm Popup command Yes, single Popup command type Squared No. of clips 8 Type of clips Standard

Accessories included



Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket, Automatic pop - up with roudn rotary control





Compatible Accessories





Siphon single bowl sinks (dishwasher connection included)

CB28QU



Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm

COL19H



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

DB34



St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth

KITFD075



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITSLTRND1



Bowl automatic pop up Rondò waste kit with rectangular overflow and round knob

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

KITFD050



Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITFD100



Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

STABMIX



Tap stabiliser



Symbols glossary



Cupboard width required for sink installation.



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Flat: Installation of product with flat edge.



Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

Double tap hole

The sink is easily reversible, making it possible to create any type of kitchen composition

Pop-up command

The pop-up command allows the sink drain to be opened and closed remotly with a simple gesture and without the need to touch the plug directly, increasing convenience and hygiene in the kitchen

Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area