

LFT50RS

Sink material Stainless steel
Type Welded bowl
No. of bowls 1
EAN code 8017709210335



Aesthetics



| | | | |
|------------------|-----------------|-----------------------------------|--------------------|
| Aesthetic | Universale | Building in type | Flush fitted, Flat |
| Colour | Stainless steel | Logo | Embossed |
| Finishing | Brushed | Tap hole / precut tap hole | 2 Tapholes |
| Series | Mira | | |

| | Bowl type | Bowl dimensions, WxDxH (mm) | Bowl depth (mm) | Radius corner bowl | Overflow | Strainer position | Strainer dimension |
|------|----------------|-----------------------------|-----------------|--------------------|-------------------|-------------------|--------------------|
| Bowl | Minimum radius | 500 x 400 x 200 | 200 | 15 | Yes, flush fitted | Wall position | 3.5" |

Technical Features




| | | | |
|---------------------------------------|----------------|---------------------------|-------------|
| Dimensions of the product (mm) | 200x561x510 mm | Tap hole diameter | 35 mm |
| Cutout dimension topmount (mm) | 530 x 490 mm | Popup command | Yes, single |
| Height from kitchen top | 1 mm | Popup command type | Squared |
| Base unit size | 60 cm | No. of clips | 10 |
| Tap hole | 2 | Type of clips | Standard |

Accessories included

Accessories for
installation

Strainer, Savespace siphon
with dishwasher outlet
connection, Fixing clips,
Gasket, Automatic pop - up
with roudn rotary control



Compatible Accessories



3712

Siphon single bowl sinks (dishwasher connection included)



CB28QU

Single HPL chopping board for minimum radius, oak, measures 280 x 418 H 12 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITSLTRND1

Bowl automatic pop up Rondò waste kit with rectangular overflow and round knob



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100





Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



STABMIX

Tap stabiliser

Symbols glossary

- | | | | |
|--|--|---|---|
|  | Cupboard width required for sink installation. |  | Sink depth - depending on the model, the depth can be from 13 to 24,5. |
|  | Flat: Installation of product with flat edge. |  | Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit. |

Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

Double tap hole

The sink is easily reversible, making it possible to create any type of kitchen composition

Pop-up command

The pop-up command allows the sink drain to be opened and closed remotely with a simple gesture and without the need to touch the plug directly, increasing convenience and hygiene in the kitchen

Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area