

LFT77RS

Sink material	Stainless steel
Type	Welded bowl
No. of bowls	1
EAN code	8017709210342



Aesthetics



Aesthetic	Universale	Building in type	Flush fitted, Flat
Colour	Stainless steel	Logo	Embossed
Finishing	Brushed	Tap hole / precut tap hole	2 Tapholes
Series	Mira		

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	710 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Technical Features




Dimensions of the product (mm)	200x770x510 mm	Tap hole diameter	35 mm
Cutout dimension topmount (mm)	740 x 490 mm	Popup command	Yes, single
Height from kitchen top	1 mm	Popup command type	Squared
Base unit size	80 cm	No. of clips	10
Tap hole	2	Type of clips	Standard

Accessories included

**Accessories for
installation**

Strainer, Savespace siphon
with dishwasher outlet
connection, Fixing clips,
Gasket, Automatic pop - up
with round rotary control



Compatible Accessories

3712

Siphon single bowl sinks (dishwasher connection included)

CB28QU

Single HPL chopping board for minimum radius, oak, measures 280 x 418 H 12 mm

COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth

KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITSLTRND1

Bowl automatic pop up Rondò waste kit with rectangular overflow and round knob

CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

**COL19**

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 30 mm

**COL36**

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

**KITFD050**

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

**KITFD100**

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

STABMIX

Tap stabiliser



Symbols glossary



Cupboard width required for sink installation.



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Flat: Installation of product with flat edge.



Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.

Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

Double tap hole

The sink is easily reversible, making it possible to create any type of kitchen composition

Pop-up command

The pop-up command allows the sink drain to be opened and closed remotely with a simple gesture and without the need to touch the plug directly, increasing convenience and hygiene in the kitchen

Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area