

LFT861D

Sink material Type No. of bowls Drainer EAN code Stainless steel Welded sink 1 Right 8017709210441



Aesthetics

ГØ	
Aes	thetic

Series Colour Finishing Universale Mira Stainless steel scotch Brite

Building in type Logo Tap hole / precut tap hole Flush fitted, Flat Embossed 2 Tapholes

	Bowl type LH	Bowl thickness LH (mm)	Bowl dimensions LH, WxDxA (mm)	LH Bowl depth (mm)	Radius corner left bowl	Overflow LH bowl	Strainer position LH bowl	Strainer dimension LH bowl
LH Bowl	Minimum radius	1	340 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Technical Features



Frame thickness	0,7 mm	Tap hole diameter	35 mm
Frame depth (mm)	18	Popup command	Yes, single
Dimensions of the	218x870x510 mm	Popup command type	Squared
product (mm)		Drainer inclination	2 °
Cutout dimension	840 x 480 mm	Gasket type	Sealing paste
topmount (mm)		No. of clips	10
Undermount cutout	5 mm	·	
radius		Type of clips	Standard
Height from kitchen top	1 mm		
Base unit size	45 cm		
Tap hole	2		



Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket, Automatic pop - up with roudn rotary control





Compatible Accessories



3712

Siphon single bowl sinks (dishwasher connection included)

CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITSLTRND1

Bowl automatic pop up Rondò waste kit with rectangular overflow and round knob





CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

STABMIX

Tap stabiliser





Alternative products

LFT861S



Colour: Stainless steel



Symbols glossary



Cupboard width required for sink installation

Sink depth - depending on the model, the depth can be from13 to 24,5

1

Flat: Installation of productwith flat edge.

r	VI
н	12

Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

Drainer

The drawer allows dishes, cutlery and kitchen utensils to be placed directly on the sink after washing: excess water can drain into the sink, allowing for natural drying

Double tap hole

The sink is easily reversible, making it possible to create any type of kitchen composition

Pop-up command

The pop-up command allows the sink drain to be opened and closed remotly with a simple gesture and without the need to touch the plug directly, increasing convenience and hygiene in the kitchen

Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area