

LFT862

Stainless steel Sink material Welded sink Type

No. of bowls 2

EAN code 8017709210434



Aesthetics





Aesthetic Universale Building in type Flush fitted. Flat Colour Stainless steel **Embossed** Logo **Finishing** Scotch Brite Tap hole / precut tap 2 Tapholes hole

Series Mira

Bowl Bowl Bowl Radius corner Bowl Strainer Strainer Overflow thickness dimensions, depth type RH right bowl (mm) position dimension (mm) WxDxH (mm) (mm) RHMinimum Yes, flush Wall 1 340 x 400 x 200 200 15 3.5" radius Bowl fitted position LH Minimum Wall 1 340 x 400 x 200 200 15 3.5"

Technical Features

radius



Bowl

Frame thickness Frame depth (mm) 15

Dimensions of the

product (mm)

Cutout dimension topmount (mm)

0.7 mm

5 mm

215x870x510 mm

840 x 480 mm

Tap hole diameter Popup command Popup command type

Dividing wall width

Yes, double Squared 75 mm

35 mm

position

Gasket type Sealing paste

No. of clips 12 Standard Type of clips

Undermount cutout radius

SMEG SPA 22/11/2025




Height from kitchen top 1 mm
Base unit size 90 cm
Tap hole 2

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket, Automatic pop - up with roudn rotary control



SMEG SPA 22/11/2025



Compatible Accessories





Siphon double bowls sinks (dishwasher connection included)

CB28QU



Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm

COL19H



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

DB34



St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth

KITFD075



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITSLTRND2



2 Bowls automatic Rondò pop up waste kit with rectangular overflow and round knob

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

KITFD050



Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITFD100



Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

STABMIX



Tap stabiliser

SMEG SPA 22/11/2025



Symbols glossary



Cupboard width required for sink installation.



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Flat: Installation of product with flat edge.



Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.

SMEG SPA 22/11/2025