

LFTG861D

Sink material Stainless steel
Type Welded sink

No. of bowls 1
Drainer Right

EAN code 8017709282400



Aesthetics



AestheticUniversaleBuilding in typeFlatColourStainless steelLogoEmbossedFinishingScotch BriteTap hole / precut tap2 Tapholes

Series Mira hole

	Bowl type LH	Bowl thickness LH (mm)	Bowl dimensions LH, WxDxA (mm)	LH Bowl depth (mm)	Radius corner left bowl	Overflow LH bowl	Strainer position LH bowl	Strainer dimension LH bowl
LH Bowl	Minimum radius	1	450 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Technical Features



Frame thickness 0,7 mm Tap hole diameter 35 mm
Frame depth (mm) 18 Popup command Yes, single
Dimensions of the 218x870x510 mm Popup command type Squared

product (mm)

Drainer inclination 2

Cutout dimension 840 x 480 mm Gasket type Sealing paste topmount (mm)

Undermount cutout 5 mm No. of clips 10

radius Type of clips Standard Height from kitchen top 1 mm Possibility to install Yes


Base unit size 60 cm Possibility to install Yes
Tap hole 2



Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket, Automatic pop - up with roudn rotary control





Compatible Accessories





Siphon single bowl sinks (dishwasher connection included)

CB28QU



Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm

COL19H



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

DB34



St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth

KITFD075



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITSLTRND1



Bowl automatic pop up Rondò waste kit with rectangular overflow and round knob

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

KITFD050



Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITFD100



Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

STABMIX



Tap stabiliser



Symbols glossary



Cupboard width required for sink installation.



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Flat: Installation of product with flat edge.