

LLR116-2

Sink material Stainless steel Welded sink Type

No. of bowls 2

Drainer Reversible

EAN code 8017709218607



Aesthetics



Universale **Aesthetic Building in type** Ultra-low profile Colour Stainless steel Logo **Embossed**

Finishing Brushed Tap hole / precut tap 2 Tapholes hole

Series Alba

	Bowl type RH	Bowl thickness (mm)	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Traditional	0.7	340 x 400 x 210	210	80	Yes, traditional	Side bowl	3.5"
LH Bowl	Traditional	0.7	340 x 400 x 210	210	80		Side bowl	3.5"

Technical Features



Frame thickness 0,7 mm Tap hole diameter 35 mm Frame depth (mm) 15 Popup command Yes, single Dimensions of the 225x1160x500 mm Popup command type Round

product (mm) Dividing wall width 30 mm **Cutout dimension** 1140 x 480 mm **Drainer inclination** 2 °

topmount (mm) Gasket type Sealing paste

No. of clips 10 **Undermount cutout** 15 mm radius Type of clips Standard

SMEG SPA 10/10/2025




Height from kitchen top 6 mm
Base unit size 80 cm
Tap hole 2

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket, Automatic pop - up with roudn rotary control



SMEG SPA 10/10/2025



Compatible Accessories

3713



Siphon double bowls sinks (dishwasher connection included)

CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe





Single wooden chopping board to fit STD radius 340 x 400 mm bowl



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITSLTRND2

2 Bowls automatic Rondò pop up waste kit with rectangular overflow and round knob



STABMIX

Tap stabiliser

SMEG SPA 10/10/2025



Symbols glossary



Cupboard width required for sink installation.



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Thanks to the double tap hole, most of our sinks are easily reversible, giving you the flexibility to make any type of kitchen composition.

SMEG SPA 10/10/2025