

LPR862

Sink material Stainless steel
Type Welded sink

No. of bowls 2

EAN code 8017709304713



Aesthetics



AestheticUniversaleBuilding in typeUltra-low profileSeriesAuroraLogoEmbossedColourStainless steelTap hole / precut tap2 Tapholes

Finishing Brushed hole

	Bowl type RH	Bowl thickness (mm)	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Traditional	0.6	340 x 400 x 180	180	80	Yes, traditional	Side bowl	3.5"
LH Bowl	Traditional	0.6	340 x 400 x 180	180	80		Side bowl	3.5"

Technical Features



Frame thickness 0,6 mm Tap hole 2

Frame depth (mm) 13 Tap hole diameter 35 mm Dimensions of the 193x860x500 mm Dividing wall width 30 mm

product (mm) Gasket type Sealing paste

Cutout dimension 840 x 480 mm No. of clips 8

topmount (mm) Type of clips Standard


Height from kitchen top 6 mm Base unit size 90 cm



Accessories Included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket, Blanking cap





Not included accessories



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



STABMIX

Tap stabiliser



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



KITDS

Soap dispenser chrome finishing with round knob



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



KITSLTRND2

2 Bowls automatic Rondò pop up waste kit with rectangular overflow and round knob



DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



3713

Siphon double bowls sinks (dishwasher connection included)



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



CB34

Single wooden chopping board to fit STD radius 340 x 400 mm bowl



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



Symbols glossary (TT)



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24.5



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Benefit (TT)

Two bowls

Two bowls for greater versatility and dual functionality

Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area

Double tap hole

The sink is easily reversible, making it possible to create any type of kitchen composition