

LVS292DX

| | |
|-------------------|---------------|
| Product Family | Dishwashers |
| Commercial width | 60 cm |
| Commercial height | 85 cm |
| Installation | Free-standing |
| N° baskets | 2 |
| EAN code | 8017709307196 |



Programme / Functions




| | | | |
|----------------------|---------------|----------|-----|
| N. of programmes | 5 | Mix | Yes |
| Washing temperatures | 50, 65, 70 °C | Intense | Yes |
| Soak | Yes | 1/2 load | Yes |
| ECO | Yes | | |

Options



| | | | |
|--------------------|-------------|------------------|-----|
| Delay timer option | 3-6-9 hours | Extra dry option | Yes |
|--------------------|-------------|------------------|-----|

Baskets


| | | | |
|--|--------------------------------------|---------------------------------------|-----------------------|
|  | | | |
| Basket colour | Grey | Largest loadable dish in upper basket | 25,0 cm |
| Basket components colour | Grey | Lower Basket | With 2 foldable racks |
| Handle | In plastic on upper and lower basket | Lower basket with anti-drip inserts | Yes |
| Upper Basket | With central fixed racks | Largest loadable dish in lower basket | 30,0 cm |
| Glass holder | Yes | Colour Inner Components | Green |
| Height adjustment of the upper basket | On three levels (5 cm) | Cutlery basket | Yes |

Technical Features



| | | | |
|-------------------------------|--------------------------------------|--|---|
| Width (mm) | 598 mm | Flood protection system | Total Acquastop |
| Depth (mm) | 600 mm | Water supply | Single; cold/hot water max. 60°C - energysave with hot water up to 35% |
| Product Height (mm) | 848 mm | Max water hardness | 100°FH;58°dH |
| Controls | Electronic | Drying system | Natural condenser drying, with Dry Assist + automatic door opening system at the end of the cycle |
| Display | Delayed start | Tube material | Stainless steel |
| Programme graphics | Symbols | Filter | Stainless steel |
| Salt light indicator | Light | Concealed heating element | Yes |
| Rinse aid indicator | Light | Hinges | Self balancing with fixed hinges |
| End of cycle indicator | Led on display, with acoustic signal | Adjustable feet | Just for levelling |
| Washing system | Orbital | Depth of dishwasher with open door (mm) | 1168 |
| Third spray arm | Single | Removable top | Yes, with optional KIT |
| Water softener | With electronic setting | Top cover | In plastic |


Performance / Energy Label NEW 2019



| | | | |
|--|-------------|---|------------------|
| Energy Efficiency Class | D | Programme duration | 4:10 h:min |
| Energy consumption [per 100 cycles, based on the eco programme] | 84 KWh | Airborne acoustical noise emissions | 49 dB(A) re 1 pW |
| Rated capacity (ps) | 13 | Airborne acoustical noise emission class | C |
| Water consumption [per cycle] | 12,0 litres | Energy efficiency Index (EEI) | 49,9 |

Electrical Connection

| | | | |
|------------------------|--------------|----------------------------------|--------------|
| Plug | (F;E) Schuko | Frequency (Hz) | 50 Hz |
| Connected power | 1800 W | Type of connection | Single-phase |
| Current | 10 A | Power supply cable length | 140 cm |
| Voltage | 220-240 V | | |




Not included accessories



KITPLV2

Kit extension for dishwasher and washing machine: lenght mt. 2



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks

Alternative products



LVS292DN
Colour: Black

















LVS292DB
Colour: White



LVS292DS
Colour: Silver

Symbols glossary (TT)

| | |
|---|---|
|  To improve the drying of dishes without leaving stains. |  Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time. |
|  Noise Level: Excellent insulation and special devices keep noise to a minimum. |  Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash. |
|  1/2 load: This program is designed for washing dishes not heavily soiled with partial load of the dishwasher. |  Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option. |
|  Mix: The Mix programme is suitable for mixed crockery and everyday pots and pans, without any particular incrustation. |  Soak programme: The soak programme provides a rinse to prevent dirt from drying. |
|  Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°C eliminating virtually all bacteria. |  13 place settings: Number of place settings. |
|  Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary. |  System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher. |
|  EXTRA DRY This option adds a hot rinse cycle that ensures improved drying. |  Energy efficiency class D |