

LYP862

Sink materialStainless steelTypeMonoblock sink

No. of bowls

EAN code 8017709251611



Aesthetics



AestheticUniversaleBuilding in typeStandardSeriesOmniLogoEmbossedColourStainless steelTap hole / precut tap1 Tap hole

Finishing Pre-polished hole

	Bowl type RH	Bowl thickness (mm)	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Traditional	0.6	370 * 370 * 149	150	90	Yes, traditional	Side bowl	3.5"
LH Bowl	Traditional	0.6	370 * 370 * 149	150	90		Side bowl	3.5"

Technical Features



Frame thickness 0.6 mm Tap hole 1

Frame depth (mm) 8 Tap hole diameter 35 mm

Dimensions of the 150x860x500 mm Dividing wall width 40 mm

product (mm) Gasket type Sealing paste

Cutout dimension 840 x 480 mm No. of clips 8

topmount (mm) Type of clips Standard

Type of Chps Stundard

Undermount cutout

radius

10 mm




Height from kitchen top 8 mm Base unit size 90 cm

Accessories included

Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips, Gasket





Compatible Accessories

3713



Siphon double bowls sinks (dishwasher connection included)



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



RND2V

2 Bowls standard Rondò waste kit with rectangular overflow



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



STABMIX

Tap stabiliser



Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24.5



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Benefit (TT)

Two bowls

Two bowls for greater versatility and dual functionality

Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area