


# LZ150A2

Sink material	Composite
Type	Composite sink
No. of bowls	1
Drainer	Reversible
EAN code	8017709274603



## Aesthetics

	<b>Aesthetic</b>	Universale	<b>Logo</b>	Applied/on overflow
	<b>Colour</b>	Anthracite	<b>Alternative colours available</b>	White, Cream, Beige, Cemento / Concrete
	<b>Series</b>	Rigae	<b>Tap hole / precut tap hole</b>	Prepared
	<b>Building in type</b>	Standard		

	Bowl type LH	Bowl dimensions LH, WxDxA (mm)	LH Bowl depth (mm)	Radius corner left bowl	Overflow LH bowl	Strainer position LH bowl	Strainer dimension LH bowl
LH Bowl	Traditional	420 x 480 x 210	210	70	Yes, traditional	Side bowl	3.5"

## Technical Features



<b>Characteristics composite material</b>	Antibacterial, Easy to clean, Anti-scratch, Thermal shock resistant, High temperatures resistant, Impact resistant, UV Resistant	<b>Base unit size</b>	60 cm
<b>Frame depth (mm)</b>	10	<b>Tap hole</b>	2
<b>Dimensions of the product (mm)</b>	210x1000x500 mm	<b>Tap hole diameter</b>	35 mm
<b>Cutout dimension topmount (mm)</b>	980 X 480 mm	<b>Drainer inclination</b>	2°
		<b>No. of clips</b>	10
		<b>Type of clips</b>	Standard



---

## Compatible Accessories

---



### COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



### KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



### KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



### KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



### KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

---

## Alternative products

---

**LZ150CT**

**Colour: Cement / Concrete**



**LZ150AV2**

**Colour: Oats**



**LZ150P**

**Colour: Cream**



**LZ150B**












**Colour: White**



---

## Symbols glossary

---

	Antibacterial		Antiscratch
	Cupboard width required for sink installation.		Sink depth - depending on the model, the depth can be from 13 to 24,5.
	Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.		Thermal shock resistant
	High temperatures resistant		Impact resistant
	Easy to clean		Thanks to the double tap hole, most of our sinks are easily reversible, giving you the flexibility to make any type of kitchen composition.
	UV protection, does not fade over time.		