

PGF30T-1



Product Family

Built-in type Ultra-low profile

Hob

Dimensions 30 cm
Power supply Electric
Type Teppanyaki
EAN code 8017709161910



Yes

Aesthetics



Aesthetic Classic

Colour Stainless steel

Finishing Satin

MaterialStainless SteelType of steelBrushed

Type of control setting Control knobs

Control knob position Front No. of controls 2

Controls colourSteel effectSerigraphy colourBlack

Programs / Functions

Total no. of cook zones 2
No. of induction cook zones 2
Power levels 9

Options



Standard cut out 494x292 mm Cleaning option

Control Lock / Child Yes

Safety

192 mm Cicuming optio



Technical Features





Front-centre - Teppanyaki - 1.40 kW - Booster 1.80 kW Rear-centre - Teppanyaki - 1.40 kW - Booster 1.80 kW

Yes

Automatic switch off

when overheat

Residual heat indicator Yes

Electrical Connection


Electrical connection 3000 W

rating (W)

Current 13 A

Voltage (V) 220-240 V

Type of electric cable Frequency (Hz) Power supply cable length Single phase 50/60 Hz 120 cm





Not included accessories

LGPGF-1

Aluminium connecting strip for PGF

6MP1PGF

6 Linea knobs for PGF hobs





Symbols glossary (TT)



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.



Knobs control