

PIP2951D




Product Family Hob

Built-in type Ultra-low profile or Fully Flushed

Dimensions90 cmPower supplyElectricTypeInduction

EAN code 8017709310073



Aesthetics





AestheticUniversaleColourBlackFinishingGlassMaterialGlassGlass typeCeramicGlass edgeStraight edgeType of control settingTouch controls

Slider Yes
Slider Red
Control knob position Front
Logo Silk screen
Serigraphy colour Grey

Program / Functions



No. of induction cook zones

Time-setting options Automatic Shutdown

No. of cooking zones with booster5Main on/off switchYesPower levels9Total no. of cook zones5

Options



















Standard cut out

Multizone Option Yes Keep warm automatic Yes

function

5 End cooking timer Pause option Yes Minute minder 1 End of cooking alarm Yes

478-482x839-844 mm

Limited Power

Advanced Eco Logic

Consumption Mode

Limited Power

2400 a 7400 - step 100 W

Yes

Yes

Yes

Consumption Mode in W Showroom Demo Option Control Lock / Child

Residual time indicator

Safety

Quick start Yes Rapid level selection Yes

Technical Features













Front-left - Induction - Single - 1.40 kW - Booster 2.10 kW - Ø 16.0 cm

Rear-left - Induction - Single - 2.30 kW - Booster 3.00 kW - Ø 21.0 cm

Central - Induction - Single - 2.30 kW - Booster 3.00 kW - Ø 25.0 cm

Yes

Yes

Rear-right - Induction - Single - 2.30 kW - Booster 3.00 kW - Ø 21.0 cm Front-right - Induction - Single - 1.40 kW - Booster 2.10 kW - Ø 16.0 cm

Automatic settina

according to pan

dimension

pan detection Yes, min 7 cm

Permanent Automatic Pot Detection with

indication of the relative

control

Automatic switch off

when overheat

Automatic switch off Yes

when overflow

Residual heat indicator Yes **Protection against** Yes

accidental start up

Electrical Connection

Electrical connection

7400 W

rating (W)

33 A Current Voltage (V) 220-240 V Voltage 2 (V) 380-415 V Type of electric cable Single phase Type of electric cable

Frequency (Hz) Power supply cable

length

Terminal box


Double phase

50/60 Hz

120 cm

5 poles







Compatible Accessories



SCRP

Induction and ceramic hobs and teppanyaki scraper



Symbols glossary

Automatic merge

Automatic merge of zones for a bigger area

<u>)</u>

...

Power booster: option allows the zone to work at full power when very intense cooking is necessary.

Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.

Touch control

The slider control panel allows you to adjust the power simply by passing your finger across the touch device.

Keep warm function: Keep warm function keeps the cooked food heated. In this mode the heating zone operates at a minimum capacity for 120 minutes and then turns off automatically.

Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.

Induction: The work of these hobs is based on the principle of electromagnetic induction. The heat is generated directly in the bottom of the pan during its contact with the hob.

Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids.

Tom ...

PAUSE_72dpi

ADVANCE

Quick selection, with one touch cooking begins at the highest level, then automatically reduces after time. Ideal for dishes that require quick boiling and then continued cooking without constant control (eg beef broth).

Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached.

Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.

Time elapsed: shows how long the cooking zone has been in use.

Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.