

SA661X2





Product Family Built-in type

Dimensions
Power supply

Type EAN code

Hob

Ultra-low profile

60 cm Electric Ceramic

8017709265731



Aesthetics



AestheticClassicColourBlackFinishingGlassMaterialGlassGlass typeCeramicGlass edgeAngled edgeType of control settingControl knobs

Control knob position Front
No. of controls 4

Controls colourSteel effectLogoSilk screenSerigraphy colourGrey

Program / Functions

No. of ceramic cook zones 4
Total no. of cook zones 4

Options

Standard cut out 490x560 mm

Technical Features



Front-left - Ceramic - Single - 1.80 kW - Ø 18.4 cm


Rear-left - Ceramic - Single - 1.20 kW - Ø 14.8 cm

Rear-right - Ceramic - Double - 1.00 - 2.20 kW - Ø 14.8 - Ø 21.4 cm

Front-right - Ceramic - Single - 1.20 kW - Ø 14.8 cm

Electrical Connection

Electrical connection 6400 W Type of electric cable Yes, Three and Single/Twosupplied rating (W) phase Current 19 A Frequency (Hz) 50/60 Hz Voltage (V) 220-240 V Power supply cable 120 cm length Voltage 2 (V) 380-415 V Terminal box 6 poles Type of electric cable Double universal





Compatible Accessories



SCRP

Induction and ceramic hobs and teppanyaki scraper



Symbols glossary



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Knobs control



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Glass ceramic: The base of the hob is made glass ceramic. Heating is performed by the heating elements Hi-Light.

Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.