


# SBC4304X




|                 |               |
|-----------------|---------------|
| Product Family  | Blast chiller |
| Category        | 45cm compact  |
| Vitality system | Yes           |
| Power supply    | Electric      |
| Heat source     | Electric      |
| Cooling type    | Fan assisted  |



## Aesthetics

|                         |                 |                                      |  |
|-------------------------|-----------------|--------------------------------------|--|
| <b>Aesthetic</b>        | Classica        | <b>Alternative colours available</b> | Stainless steel, Pure Black, Neptune Grey, Nero Lucido |
| <b>Colour</b>           | Stainless steel | <b>Glass Type</b>                    | Eclipse  |
| <b>Finishing</b>        | Fingerproof     | <b>Door</b>                          | With 2 horizontal strips                               |
| <b>Design</b>           | Flat            | <b>Handle</b>                        | Classic  |
| <b>Component finish</b> | Stainless steel | <b>Handle Colour</b>                 | Steel effect   |
| <b>Material</b>         | Stainless steel | <b>Logo</b>                          | Embossed   |
| <b>Type of steel</b>    | Brushed         |                                      |  |

## Programme / Functions

|                          |   |
|--------------------------|---|
| No. of warming functions | 4   |
| Automatic programmes     | 10  |
| N. cold functions        | 4   |
| Automatic cleaning       |  |
| Customisable recipes     | 100   |

## Controls



|                 |                                   |                 |               |
|-----------------|-----------------------------------|-----------------|---------------|
| Display / Clock | TFT graphic , colour touch screen | Control setting | Touch control |
|-----------------|-----------------------------------|-----------------|---------------|

## Options



|                                       |     |                             |                                       |
|---------------------------------------|-----|-----------------------------|---------------------------------------|
| <b>Door open alarm</b>                | Yes | <b>Cooling with probe</b>   | Yes                                   |
| <b>Minute minder</b>                  | Yes | <b>Showroom demo option</b> | Yes                                   |
| <b>Timer</b>                          | 2   | <b>Tones</b>                | Polyphonic                            |
| <b>Controls Lock / Child Safety</b>   | Yes | <b>Chronology</b>           | Yes, the last 10 functions utilized   |
| <b>Cooking with probe thermometer</b> | Yes | <b>Touch guide</b>          | Sì, a pressione prolungata su display |

## Technical Features



|                             |                 |  |                  |
|-----------------------------|-----------------|--|------------------|
| <b>Compressor type</b>      | Standard        | <b>No. of lights</b>                         | 1                |
| <b>Refrigerant gas type</b> | R290            | <b>Light type</b>                            | Halogen          |
| <b>Refrigerant Quantity</b> | 58 g            | <b>Light Power</b>                           | 1 W              |
| <b>Climatic class</b>       | SN, N, ST, T    | <b>Light when door is opened</b>             | Yes              |
| <b>Temperature control</b>  | Electronic      | <b>Upper heating element - Power</b>         | 250 W            |
| <b>Minimum Temperature</b>  | -28 °C          | <b>Door opening type</b>                     | Standard opening |
| <b>Maximum temperature</b>  | 75 °C           | <b>Safety Thermostat</b>                     | Yes              |
| <b>Cavity material</b>      | Stainless steel | <b>Heating suspended when door is opened</b> | Yes              |
| <b>No. of shelves</b>       | 3               | <b>Gross volume</b>                          | 34 l             |
| <b>Shelves type</b>         | Metal racks     |  |                  |

## Accessories Included

|                            |   |                          |                  |
|----------------------------|---|--------------------------|------------------|
| <b>Grid with back stop</b> | 1 | <b>Temperature probe</b> | Yes              |
| <b>Bottle rack grid</b>    | 1 | <b>Other</b>             | Microfiber cloth |

## Electrical Connection







|   |              |                                  |        |
|---|--------------|----------------------------------|--------|
| <b>Plug</b>                             | (F;E) Schuko | <b>Current</b>                   | 2.5 A  |
| <b>Voltage</b>                          | 220-240 V    | <b>Frequency (Hz)</b>            | 50 Hz  |
| <b>Electrical connection rating (W)</b> | 270 W        | <b>Power supply cable length</b> | 200 cm |



---

## Symbols glossary (TT)

---

|  |   |   |   |
|--|---|---|---|
|  | Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.              |  | Electric  |
|  | Automatic cleaning: a drying cycle of the cavity to be run with the door open, to eliminate any condensation formed during use. |  | Compact appliances with a height of 45 cm - perfect solution to meet the functional requirements of kitchen sets of small height. Available in several types and in different styles. |
|  | Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.                       |  | The capacity indicates the amount of usable space in the oven cavity in litres.   |