

# **SE332EB**





Product Family

Built-in Ultra-low profile

Hob

Dimensions30 cmPower supplyElectricTypeCeramic

**EAN code** 8017709233723



#### **Aesthetics**



**Aesthetics** Universal Colour Black Glass **Finishing** Material Glass Glass Type Ceramic Glass edge Angled edge Digi Touch Type of control setting Control knobs position Front Silk screen Logo Serigraphy colour Grey

## **Program / Functions**



No. of ceramic cook zones 2
No. of cooking zones with booster 2
Main on/off switch Yes
Power levels 9
Total no. of cook zones 2

### **Options**







Standard cut out

490x270 mm



Keep warm automatic

Yes

function

Show Room Demo Yes

Option

Control Lock / Child

Safety

Quick start Yes

Yes

#### **Technical Features**







Front centre - Ceramic - single - 1.20 kW - Ø 14.8 cm

Rear centre - Ceramic - double - 0.70 - 1.70 kW - Ø 12.4 - Ø 18.4 cm

Automatic switch off

when overheat

Automatic switch off Yes

when overflow

Yes Residual heat indicator Yes


#### **Electrical Connection**

Nominal power (W) 2900 W
Current 13 A
Voltage (V) 220-240 V

Voltage (V) 220-240 V Type of electric cable Single phas Frequency (Hz) 50/60 Hz Power supply cable 150 cm

length

Single phase Terminal Box 3 poles





# **Compatible Accessories**



#### SCRP

Induction and ceramic hobs and teppanyaki scraper



### Symbols glossary



Power booster: option allows the zone to work at full power when very intense cooking is necessary.



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.



Keep warm function: Keep warm function keeps the cooked food heated. In this mode the heating zone operates at a minimum capacity for 120 minutes and then turns off automatically.



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Glass ceramic: The base of the hob is made glass ceramic. Heating is performed by the heating elements Hi-Light.



Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids.



Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached.



Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.



Touch control