

SE395ETDL



| | |
|----------------|------------------------------------|
| Product Family | Hob |
| Built-in type | Ultra-low profile or Fully Flushed |
| Dimensions | 90 cm |
| Power supply | Electric |
| Type | Ceramic |
| EAN code | 8017709240912 |



Aesthetics



| | |
|-------------------------|---------------|
| Aesthetic | Universale |
| Colour | Black |
| Finishing | Glass |
| Material | Glass |
| Glass type | Ceramic |
| Glass edge | Straight edge |
| Type of control setting | Digi Touch |
| Control knob position | Front |
| Logo | Silk screen |
| Serigraphy colour | Grey |

Program / Functions



| | |
|-----------------------------------|---|
| No. of ceramic cook zones | 5 |
| No. of cooking zones with booster | 5 |
| Power levels | 9 |
| Total no. of cook zones | 5 |

Options



| | | | |
|-----------------|------------|-------------------------|-----|
| Worktop Cut-Out | 490x850 mm | Residual time indicator | Yes |
| | | Showroom Demo Option | Yes |

| | | | |
|-------------------------------------|-----|------------------------------------|-----|
| Keep warm automatic function | Yes | Control Lock / Child Safety | Yes |
| End cooking timer | 5 | Quick start | Yes |
| Minute minder | 1 | | |
| End of cooking alarm | Yes | | |

Technical Features




Front-left - Ceramic - Double - Ø 12.4 - Ø 18.0 cm
 Rear-left - Ceramic - Single - Ø 15.0 cm
 Central - Ceramic - Triple - Ø 15.0 - Ø 21.6 - Ø 29.0 cm
 Rear-right - Ceramic - Single - Ø 20.0 cm
 Front-right - Ceramic - Single - Ø 15.0 cm

| | | | |
|---|-----|--------------------------------|-----|
| Automatic switch off when overheat | Yes | Residual heat indicator | Yes |
| Automatic switch off when overflow | Yes | | |

Electrical Connection

| | | | |
|---|-------------------|----------------------------------|-------------|
| Electrical connection rating (W) | 3000 W | Frequency (Hz) | 50/60 Hz |
| Current | 13 A | Power supply cable length | 150 cm |
| Voltage (V) | 220-240 V | Terminal box | 6 poles |
| Additional connection modalities | Yes, Single phase | Plug | Not present |
| Type of electric cable supplied | Yes, Single phase | | |














Compatible Accessories



SCRP

Non-scratch hob scraper - suitable for induction and ceramic hobs

Symbols glossary

| | | | |
|---|--|---|---|
|  | Power booster: option allows the zone to work at full power when very intense cooking is necessary. |  | Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed. |
|  | This function allows you to keep cooked food warm without burner it |  | Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit. |
|  | Glass ceramic: The base of the hob is made glass ceramic. Heating is performed by the heating elements Hi-Light. |  | Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids. |
|  | Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached. |  | Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out. |
|  | Time elapsed: shows how long the cooking zone has been in use. |  | Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time. |
|  | Touch control | | |