

SE495ETD



| | |
|----------------|-------------------|
| Product Family | Hob |
| Built-in type | Ultra-low profile |
| Dimensions | 90 cm |
| Power supply | Electric |
| Type | Ceramic |
| EAN code | 8017709324254 |



Aesthetics



| | |
|-------------------------|----------------|
| Aesthetic | Universale |
| Colour | Black |
| Finishing | Glass |
| Material | Glass |
| Glass type | Ceramic |
| Glass edge | Straight edge |
| Type of control setting | Compact Slider |
| LED colours | Red |
| Control knob position | Front |
| Logo | Silk screen |
| Serigraphy colour | Grey |

Program / Functions



| | |
|-----------------------------------|---|
| No. of ceramic cook zones | 5 |
| No. of cooking zones with booster | 5 |
| Power levels | 9 |
| Total no. of cook zones | 5 |

Options



Worktop Cut-Out 490x850 mm

| | | | |
|-------------------------|-----|-------------------------------------|--------------|
| End cooking timer | 5 | Limited Power Consumption Mode | Yes |
| Minute minder | 1 | Limited Power Consumption Mode in W | 2800, 4000 W |
| End of cooking alarm | Yes | Showroom Demo Option | Yes |
| Residual time indicator | Yes | Control Lock / Child Safety | Yes |
| | | Quick start | Yes |

Technical Features



Front-left - Ceramic - Double - Ø 18.5 cm
 Rear-left - Ceramic - Single - Ø 15.0 cm
 Central - Ceramic - Triple - - Ø 29.0 cm
 Rear-right - Ceramic - Single - Ø 20.0 cm
 Front-right - Ceramic - Single - Ø 15.0 cm

Automatic switch off when overheat

Yes

Residual heat indicator


Yes

Automatic switch off when overflow

Yes

Electrical Connection

| | | | |
|----------------------------------|-------------------|----------------------------------|-----------------------------|
| Electrical connection rating (W) | 9100 W | Additional connection modalities | Yes, Double and Three Phase |
| Current | 26 A | Frequency (Hz) | 50/60 Hz |
| Voltage (V) | 220-240 V | Power supply cable length | 150 cm |
| Voltage 2 (V) | 380-415 V | Terminal box Plug | 6 poles Not present |
| Type of electric cable installed | Yes, Single phase | | |















Compatible Accessories



SCRP

Non-scratch hob scraper - suitable for induction and ceramic hobs

Symbols glossary

| | | | |
|--|--|---|---|
|  | Power booster: option allows the zone to work at full power when very intense cooking is necessary. |  | Ultra-low profile: Installation of product with flat edge - height of 1 mm. |
|  | Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed. |  | Compact Slider intuitive and easy to use |
|  | ECO-logic: option allows you to restrict the power limit of the appliance real energy saving. |  | Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit. |
|  | Glass ceramic: The base of the hob is made glass ceramic. Heating is performed by the heating elements Hi-Light. |  | Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids. |
|  | Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached. |  | Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out. |
|  | Time elapsed: shows how long the cooking zone has been in use. |  | Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time. |